

ECH-U1H182JX5

ECH-U1H182JX5 Information

| w | wineisensterom | ECH-U1H182JX5 Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 1800PF 5% 50VDC 0805 0805 (2012 Metric) For the pricing/inventory/lead time, please contact | |
|----|------------------|---|-----------------|
| Fo | r Reference Only | Website: https://www.heisener.com E-mail: salesdept@heisener.com | Request a Quote |

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECH-U1H182JX5 Specifications

| ManufacturerPanasonic Electronic ComponentsCapacitorsCapacitorsFilm CapacitorsFilm CapacitorsPackage0805 (2012 Metric)SeriesECH-U(X)Capacitance1800pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-5°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.043" (1.10mm)Height - Seated (Max)-ApplicationsSolder PadsLead Spacing-ApplicationsGeneral Purpose | | |
|---|------------------------------------|---|
| CategoryCapacitorsFilm CapacitorsPackage0805 (2012 Metric)SeriesECH-U(X)Capacitance1800pFtolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.043" (1.10mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-Features- | Manufacturer Part Number | ECH-U1H182JX5 |
| Film CapacitorsPackage0805 (2012 Metric)SeriesECH-U(X)Capacitance1800pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.043" (1.10mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-Features-Features- | Manufacturer | Panasonic Electronic Components |
| Package0805 (2012 Metric)SeriesECH-U(X)Capacitance1800pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.043" (1.10mm)Height - Seated (Max)Solder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-Features- | Category | Capacitors |
| SeriesECH-U(X)Capacitance1800pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0.079" L x 0.049" W (2.00mm x 1.25mm)Bieght - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | | Film Capacitors |
| Capacitance1800pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Package | 0805 (2012 Metric) |
| Tolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.043" (1.10mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Series | ECH-U(X) |
| Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)Oldar" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Capacitance | 1800pF |
| Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Tolerance | ±5% |
| Dielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Voltage Rating - AC | - |
| ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Voltage Rating - DC | 50V |
| Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Dielectric Material | Polyphenylene Sulfide (PPS), Metallized - Stacked |
| Mounting TypeSurface MountPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | ESR (Equivalent Series Resistance) | - |
| Package / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Operating Temperature | -55°C ~ 125°C |
| Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Mounting Type | Surface Mount |
| Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Package / Case | 0805 (2012 Metric) |
| TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures- | Size / Dimension | 0.079" L x 0.049" W (2.00mm x 1.25mm) |
| Lead Spacing-ApplicationsGeneral PurposeFeatures- | Height - Seated (Max) | 0.043" (1.10mm) |
| ApplicationsGeneral PurposeFeatures- | Termination | Solder Pads |
| Features - | Lead Spacing | - |
| | Applications | General Purpose |
| Report errors? | Features | - |
| | | Report error |

ECH-U1H182JX5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECH-U1H182JX5 Payment Methods



ECH-U1H182JX5 Shipping Methods



If you have any question about ECH-U1H182JX5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com