

# ECH-U1H472GX5

#### **ECH-U1H472GX5 Information**

www.heisener.com	 ECH-U1H472GX5 Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 4700PF 2% 50VDC 1206 1206 (3216 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### ECH-U1H472GX5 Specifications

ManufacturerPanasonic Electronic ComponentsCapacitorsCapacitorsFilm CapacitorsFilm CapacitorsPackage1206 (3216 Metric)SeriesECH-U(X)Capacitance4700pFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-5°C ~ 125°CVoltage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral Purpose		
CategoryCapacitorsFilm CapacitorsPackage1206 (3216 Metric)SeriesECH-U(X)Capacitance4700pFtolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-Features-	Manufacturer Part Number	ECH-U1H472GX5
Film CapacitorsPackage1206 (3216 Metric)SeriesECH-U(X)Capacitance4700pFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)General PurposeLead Spacing-ApplicationsGeneral PurposeFeatures-Seatures-	Manufacturer	Panasonic Electronic Components
Package1206 (3216 Metric)SeriesECH-U(X)Capacitance4700pFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)Solder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-Features-	Category	Capacitors
SeriesECH-U(X)Capacitance4700pFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.43" (1.10mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-		Film Capacitors
Capacitance4700pFTolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)Solder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package	1206 (3216 Metric)
Tolerance±2%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Series	ECH-U(X)
Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)Solder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Capacitance	4700pF
Voltage Rating - DC50VDielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Tolerance	±2%
Dielectric MaterialPolyphenylene Sulfide (PPS), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	50V
Operating Temperature-55°C ~ 125°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyphenylene Sulfide (PPS), Metallized - Stacked
Mounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-
Package / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 125°C
Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Mounting Type	Surface Mount
Height - Seated (Max)0.043" (1.10mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package / Case	1206 (3216 Metric)
TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Lead Spacing-ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.043" (1.10mm)
ApplicationsGeneral PurposeFeatures-	Termination	Solder Pads
Features -	Lead Spacing	-
	Applications	General Purpose
Report errors?	Features	-
		Report errors?

#### **ECH-U1H472GX5** Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### ECH-U1H472GX5 Payment Methods



#### ECH-U1H472GX5 Shipping Methods



If you have any question about ECH-U1H472GX5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com