



### **ECJ-2VC1H030C Information**

Part Number ECJ-2VC1H030C

Manufacturer Panasonic Electronic Components

**Category** Capacitors

**Ceramic Capacitors** 

**Description** CAP CER 3PF 50V C0G/NP0 0805

Package 0805 (2012 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ECJ-2VC1H030C Specifications**

Manufacturer Part Number         ECJ-2VC1H030C           Manufacturer         Panasonic Electronic Components           Category         Capacitors           Package         0805 (2012 Metric)           Series         ECJ           Capacitance         3pF           Tolerance         ±0.25pF           Voltage - Rated         50V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0805 (2012 Metric)           Size / Dimension         0.079" L x 0.049" W (2.00mm x 1.25mm)           Height - Seated (Max)         -           Thickness (Max)         0.028" (0.70mm)           Lead Spacing         -           Lead Style         -		
Category         Capacitors           Package         0805 (2012 Metric)           Series         ECJ           Capacitance         3pF           Tolerance         ±0.25pF           Voltage - Rated         50V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0805 (2012 Metric)           Size / Dimension         0.079" L x 0.049" W (2.00mm x 1.25mm)           Height - Seated (Max)         -           Thickness (Max)         0.028" (0.70mm)           Lead Spacing         -           Lead Style         -	Manufacturer Part Number	ECJ-2VC1H030C
Package         0805 (2012 Metric)           Series         ECJ           Capacitance         3pF           Tolerance         ±0.25pF           Voltage - Rated         50V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0805 (2012 Metric)           Size / Dimension         0.079" L x 0.049" W (2.00mm x 1.25mm)           Height - Seated (Max)         -           Thickness (Max)         0.028" (0.70mm)           Lead Spacing         -           Lead Style         -	Manufacturer	Panasonic Electronic Components
Package         0805 (2012 Metric)           Series         ECJ           Capacitance         3pF           Tolerance         ±0.25pF           Voltage - Rated         50V           Temperature Coefficient         C0G, NPO           Operating Temperature         -55°C ~ 125°C           Features         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0805 (2012 Metric)           Size / Dimension         0.079" L x 0.049" W (2.00mm x 1.25mm)           Height - Seated (Max)         -           Thickness (Max)         0.028" (0.70mm)           Lead Spacing         -           Lead Style         -	Category	Capacitors
Series         ECJ           Capacitance         3pF           Tolerance         ±0.25pF           Voltage - Rated         50V           Temperature Coefficient         COG, NPO           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0805 (2012 Metric)           Size / Dimension         0.079" L x 0.049" W (2.00mm x 1.25mm)           Height - Seated (Max)         -           Thickness (Max)         0.028" (0.70mm)           Lead Spacing         -           Lead Style         -		Ceramic Capacitors
Capacitance         3pF           Tolerance         ±0.25pF           Voltage - Rated         50V           Temperature Coefficient         COG, NPO           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0805 (2012 Metric)           Size / Dimension         0.079" L x 0.049" W (2.00mm x 1.25mm)           Height - Seated (Max)         -           Thickness (Max)         0.028" (0.70mm)           Lead Spacing         -           Lead Style         -	Package	0805 (2012 Metric)
Tolerance         ±0.25pF           Voltage - Rated         50V           Temperature Coefficient         C0G, NP0           Operating Temperature         -55°C ~ 125°C           Features         -           Ratings         -           Applications         General Purpose           Failure Rate         -           Mounting Type         Surface Mount, MLCC           Package / Case         0805 (2012 Metric)           Size / Dimension         0.079" L x 0.049" W (2.00mm x 1.25mm)           Height - Seated (Max)         -           Thickness (Max)         0.028" (0.70mm)           Lead Spacing         -           Lead Style         -	Series	ECJ
Voltage - Rated50VTemperature CoefficientC0G, NP0Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.028" (0.70mm)Lead Spacing-Lead Style-	Capacitance	3pF
Temperature CoefficientCOG, NPOOperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.028" (0.70mm)Lead Spacing-Lead Style-	Tolerance	±0.25pF
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0805 (2012 Metric)Size / Dimension0.079" L x 0.049" W (2.00mm x 1.25mm)Height - Seated (Max)-Thickness (Max)0.028" (0.70mm)Lead Spacing-Lead Style-	Voltage - Rated	50V
Features - General Purpose - G	Temperature Coefficient	C0G, NP0
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.028" (0.70mm) Lead Spacing - Lead Style - Surface Mount, MLCC	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.028" (0.70mm) Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.028" (0.70mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0805 (2012 Metric) Size / Dimension 0.079" L x 0.049" W (2.00mm x 1.25mm) Height - Seated (Max) - Thickness (Max) 0.028" (0.70mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case       0805 (2012 Metric)         Size / Dimension       0.079" L x 0.049" W (2.00mm x 1.25mm)         Height - Seated (Max)       -         Thickness (Max)       0.028" (0.70mm)         Lead Spacing       -         Lead Style       -	Failure Rate	-
Size / Dimension       0.079" L x 0.049" W (2.00mm x 1.25mm)         Height - Seated (Max)       -         Thickness (Max)       0.028" (0.70mm)         Lead Spacing       -         Lead Style       -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max)  Thickness (Max)  Lead Spacing  Lead Style  -  -  -  -  -  -  -  -  -  -  -  -  -	Package / Case	0805 (2012 Metric)
Thickness (Max) 0.028" (0.70mm)  Lead Spacing -  Lead Style -	Size / Dimension	0.079" L x 0.049" W (2.00mm x 1.25mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.028" (0.70mm)
	Lead Spacing	-
	Lead Style	-
Report errors?		Report errors?

### **ECJ-2VC1H030C Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ECJ-2VC1H030C Payment Methods**





















### **ECJ-2VC1H030C Shipping Methods**













If you have any question about ECJ-2VC1H030C, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com