



ECJ-ZEB1H102K Information

Part Number ECJ-ZEB1H102K

Manufacturer Panasonic Electronic Components

Category Capacitors

Ceramic Capacitors

Description CAP CER 1000PF 50V X7R 0201

Package 0201 (0603 Metric)

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECJ-ZEB1H102K Specifications

Manufacturer Part Number ECJ-ZEB1H102K Manufacturer Panasonic Electronic Components Category Capacitors Package 0201 (0603 Metric) Series ECJ Capacitance 1000pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -		
Category Capacitors Package 0201 (0603 Metric) Series ECJ Capacitance 1000pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Manufacturer Part Number	ECJ-ZEB1H102K
Package O201 (0603 Metric) Series ECJ Capacitance 1000pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Manufacturer	Panasonic Electronic Components
Package 0201 (0603 Metric) Series ECJ Capacitance 1000pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Category	Capacitors
Series ECJ Capacitance 1000pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -		Ceramic Capacitors
Capacitance 1000pF Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Package	0201 (0603 Metric)
Tolerance ±10% Voltage - Rated 50V Temperature Coefficient X7R Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Series	ECJ
Voltage - Rated50VTemperature CoefficientX7ROperating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0201 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-	Capacitance	1000pF
Temperature Coefficient Operating Temperature -55°C ~ 125°C Features - Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style X7R A7R A7R A7R A7R - 55°C ~ 125°C - 020 General Purpose General Purpose Coencil Purpose 1 Coencil Purpose Coenci	Tolerance	±10%
Operating Temperature-55°C ~ 125°CFeatures-Ratings-ApplicationsGeneral PurposeFailure Rate-Mounting TypeSurface Mount, MLCCPackage / Case0201 (0603 Metric)Size / Dimension0.024" L x 0.012" W (0.60mm x 0.30mm)Height - Seated (Max)-Thickness (Max)0.013" (0.33mm)Lead Spacing-Lead Style-	Voltage - Rated	50V
Features Ratings - Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing Lead Style -	Temperature Coefficient	X7R
Ratings - General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style - Surface Mount, MLCC	Operating Temperature	-55°C ~ 125°C
Applications General Purpose Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Features	-
Failure Rate - Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Ratings	-
Mounting Type Surface Mount, MLCC Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Applications	General Purpose
Package / Case 0201 (0603 Metric) Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Failure Rate	-
Size / Dimension 0.024" L x 0.012" W (0.60mm x 0.30mm) Height - Seated (Max) - Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Mounting Type	Surface Mount, MLCC
Height - Seated (Max) Thickness (Max) Lead Spacing Lead Style - - - - - - - - - - - - -	Package / Case	0201 (0603 Metric)
Thickness (Max) 0.013" (0.33mm) Lead Spacing - Lead Style -	Size / Dimension	0.024" L x 0.012" W (0.60mm x 0.30mm)
Lead Spacing - Lead Style -	Height - Seated (Max)	-
Lead Style -	Thickness (Max)	0.013" (0.33mm)
·	Lead Spacing	-
Report errors?	Lead Style	-
•		Report errors?

ECJ-ZEB1H102K Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECJ-ZEB1H102K Payment Methods



















ECJ-ZEB1H102K Shipping Methods













If you have any question about ECJ-ZEB1H102K, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com