



ECL10US12-E Information



For Reference Only

Part Number ECL10US12-E Manufacturer XP Power

Category Power Supplies - Board Mount

AC DC Converters

Description AC/DC CONVERTER 12V 10W

Package 4-DIP Module

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECL10US12-E Specifications

Manufacturer Part NumberECL10US12-EManufacturerXP PowerCategoryPower Supplies - Board MountAC DC ConvertersPackage4-DIP ModuleSeriesECLTypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)830mAPower (Watts)10WApplicationsITE (Commercial)FeaturesOVP, SCPOperating Temperature-20°C ~ 70°C (With Derating)Efficiency78%		
Category Power Supplies - Board Mount AC DC Converters Package 4-DIP Module Series ECL Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) 10W Applications ITE (Commercial) Features OVP, SCP Operating Temperature Power (With Derating)	Manufacturer Part Number	ECL10US12-E
PackageAC DC ConvertersPackage4-DIP ModuleSeriesECLTypeEnclosedNumber of Outputs1Voltage - Input85 ~ 264 VACVoltage - Output 112VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)830mAPower (Watts)10WApplicationsITE (Commercial)FeaturesOVP, SCPOperating Temperature-20°C ~ 70°C (With Derating)	Manufacturer	XP Power
Package 4-DIP Module Series ECL Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 830mA Power (Watts) 10W Applications ITE (Commercial) Features OVP, SCP Operating Temperature -20°C ~ 70°C (With Derating)	Category	Power Supplies - Board Mount
Series ECL Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 830mA Power (Watts) 10W Applications ITE (Commercial) Features OVP, SCP Operating Temperature -20°C ~ 70°C (With Derating)		AC DC Converters
Type Enclosed Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 830mA Power (Watts) 10W Applications ITE (Commercial) Features OVP, SCP Operating Temperature -20°C ~ 70°C (With Derating)	Package	4-DIP Module
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Features Over, SCP Operating Temperature 1 Separations 1 Current - Output (Max) Sover (With Derating)	Series	ECL
Voltage - Input 85 ~ 264 VAC Voltage - Output 1 12V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications Features OVP, SCP Operating Temperature 85 ~ 264 VAC 12V 85 ~ 264 VAC 12V - 12V	Туре	Enclosed
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features OVP, SCP Operating Temperature 12V 12V 12V 12V 12V 12V 12V 12	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features OVP, SCP Operating Temperature -20°C ~ 70°C (With Derating)	Voltage - Input	85 ~ 264 VAC
Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features Over, SCP Operating Temperature -20°C ~ 70°C (With Derating)	Voltage - Output 1	12V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features OVP, SCP Operating Temperature -20°C ~ 70°C (With Derating)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) Applications ITE (Commercial) Features OVP, SCP Operating Temperature -20°C ~ 70°C (With Derating)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial) Features OVP, SCP Operating Temperature -20°C ~ 70°C (With Derating)	Voltage - Output 4	-
Applications ITE (Commercial) Features OVP, SCP Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)	Current - Output (Max)	830mA
Features OVP, SCP Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)	Power (Watts)	10W
Operating Temperature $-20^{\circ}\text{C} \sim 70^{\circ}\text{C}$ (With Derating)	Applications	ITE (Commercial)
	Features	OVP, SCP
Efficiency 78%	Operating Temperature	-20°C ~ 70 °C (With Derating)
·	Efficiency	78%
Mounting Type Through Hole	Mounting Type	Through Hole
Package / Case 4-DIP Module	Package / Case	4-DIP Module
Size / Dimension 2.06" L x 1.07" W x 0.91" H (52.3mm x 27.2mm x 23.0mm)	Size / Dimension	2.06" L x 1.07" W x 0.91" H (52.3mm x 27.2mm x 23.0mm)
Report errors		Report errors?

ECL10US12-E Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECL10US12-E Payment Methods





















ECL10US12-E Shipping Methods













If you have any question about ECL10US12-E, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com