

# ECM40DCCT

uest a Quote

## **ECM40DCCT Information**

Heisener.com	Part Number	ECM40DCCT	
	Manufacturer	Sullins Connector Solutions	
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors	
	Description	CONN EDGE DUAL FMALE 80POS 0.156	
	Package	-	
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **ECM40DCCT Specifications**

Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialOldContact Finish ThicknessGoldContact TypeHairpin BellowsColorBlue			
CategoryConnectors, InterconnectsPackage-Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions/Bay/Row0.062" (1.57mm)Number of Positions0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeNonghe Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness0.901" (0.76µm)Contact TypeHairpin BellowsContact TypeBlueFange FeatureFush Mount, Top Opening, Threaded Insert, 4-40	Manufacturer Part Number	ECM40DCCT	
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeSolderContact MaterialSolderContact Finish Thickness30µin (0.76µm)Contact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsContact TypeBlueFange FeatureFush Mount, Top Opening, Threaded Insert, 4-40	Manufacturer	Sullins Connector Solutions	
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions/Bay/Row80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlueFaquee FeatureFlush Mount, Top Opening, Threaded Insert, 4-40	Category	Connectors, Interconnects	
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleContact MaterialSolderContact Finish ThicknessGoldContact Finish Thickness30µin (0.76µm)Contact TypeHaipin BellowsColorBlueFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40		Card Edge Connectors - Edgeboard Connectors	
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact FinishGoldContact FinishGoldContact TypeJupi (0.76µm)Contact TypeBileColorBileFage FeaturesFinish Mount, Top Opening, Threaded Insert, 4-40	Package	-	
GenderFemaleNumber of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeConder Hole, Right AngleTerminationSolderContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBueFlange FeatureeFlush Mount, Top Opening, Threaded Insert, 4-40	Series	-	
Number of Positions/Bay/Row40Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type1fnough Hole, Right AngleTerminationSolderContact MaterialGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlueFange FeatureFush Mount, Top Opening, Threaded Insert, 4-40	Card Type	Non Specified - Dual Edge	
Number of Positions80Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeBlueFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40	Gender	Female	
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.156" (3.96mm)Features-Mounting Type-TerminationSolderContact MaterialPhosphor BronzeContact Finish ThicknessGoldContact TypeHairpin BellowsColorBlueFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40	Number of Positions/Bay/Row	40	
Number of Rows2Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeBlueFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40	Number of Positions	80	
Pitch0.156" (3.96mm)Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlueFlange FeatureFush Mount, Top Opening, Threaded Insert, 4-40	Card Thickness	0.062" (1.57mm)	
Features-Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlueFange FeatureFush Mount, Top Opening, Threaded Insert, 4-40	Number of Rows	2	
Mounting TypeThrough Hole, Right AngleTerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlueFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40	Pitch	0.156" (3.96mm)	
TerminationSolderContact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlueFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40	Features	-	
Contact MaterialPhosphor BronzeContact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlueFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40	Mounting Type	Through Hole, Right Angle	
Contact FinishGoldContact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlueFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40	Termination	Solder	
Contact Finish Thickness30µin (0.76µm)Contact TypeHairpin BellowsColorBlueFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40	Contact Material	Phosphor Bronze	
Contact TypeHairpin BellowsColorBlueFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40	Contact Finish	Gold	
ColorBlueFlange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40	Contact Finish Thickness	30µin (0.76µm)	
Flange FeatureFlush Mount, Top Opening, Threaded Insert, 4-40	Contact Type	Hairpin Bellows	
	Color	Blue	
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Flange Feature	Flush Mount, Top Opening, Threaded Insert, 4-40	
	Operating Temperature	$-65^{\circ}C \sim 125^{\circ}C$	
Report errors?		Report errors?	

#### **ECM40DCCT Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE EUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **ECM40DCCT Payment Methods**



### **ECM40DCCT Shipping Methods**



If you have any question about ECM40DCCT, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com