

ECNR.25 Information

Heisener.com

Manuf

Part Number ECNR.25 Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description UL CLASS RK-5 TIME DELAY

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECNR.25 Specifications

Manufacturer Part NumberECNR.25ManufacturerEatonCategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesECNRFuse TypeCartridgeCurrent Rating250mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)		
CategoryCircuit ProtectionBectrical, Specialty FusesPackageCartridge, Non-StandardSeriesECNRFuse TypeCartridgeCurrent Rating250mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Manufacturer Part Number	ECNR.25
Blectrical, Specialty Fuses Package Cartridge, Non-Standard Series ECNR Fuse Type Cartridge Current Rating 250mA Voltage Rating - AC Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Siev Non-Standard Size / Dimension Electrical, Specialty Fuses Cartridge, Non-Standard Size / Dimension Electrical, Industrial Cartridge, Non-Standard Size / Dimension Electrical, Industrial Cartridge, Non-Standard Size / Dimension Electrical, Industrial Cartridge, Non-Standard Size / Dimension Size / Dimension Cartridge, Non-Standard Size / Dimension	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesECNRFuse TypeCartridgeCurrent Rating250mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Category	Circuit Protection
SeriesECNRFuse TypeCartridgeCurrent Rating250mAVoltage Rating - AC250VVoltage Rating - DC125VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)		Electrical, Specialty Fuses
Fuse Type Current Rating Current Rating 250mA Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Cartridge 250mA Catrridge Caso Catrridge Cartridge, Non-Standard Size / Dimension Catrridge Caso Catrridge, Non-Standard	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 250V Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250mA 250mA 250m A 250V CE, CSA CE, CSA CE, CSA CE, CSA CE, CSA Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Series	ECNR
Voltage Rating - AC Voltage Rating - DC 125V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 250V 250V 250V 260V 125V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 125V 125	Current Rating	250mA
Response Time Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Slow Slow Slow Slow Approvals - CE, CSA, Industrial - CE, CSA, UL CE, CSA, UL - C	Voltage Rating - AC	250V
Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Voltage Rating - DC	125V
Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Fracking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension CE, CSA, UL CARTRIDATE OF CONTROL OF CONTR	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Approvals	CE, CSA, UL
Mounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 0.560" Dia x 2.00" L (14.22mm x 50.80mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	0.560" Dia x 2.00" L (14.22mm x 50.80mm)
·		Report errors?

ECNR.25 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECNR.25 Payment Methods



















ECNR.25 Shipping Methods













If you have any question about ECNR.25, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com