



### **ECNR300 Information**

Heisener.com

Part Number ECNR300
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

**Description** UL CLASS RK-5 TIME DELAY

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ECNR300 Specifications**

Manufacturer Part NumberECNR300ManufacturerEatonCategoryCircuit ProtectionBectrical, Specialty FusesPackageCartridge, Non-StandardSeriesECNRFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.380" Dia x 8.630" L (60.45mm x 219.20mm)Report errors?		
Category Circuit Protection Electrical, Specialty Fuses  Package Cartridge, Non-Standard Series ECNR Fuse Type Cartridge Current Rating 300A Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge, Non-Standard Size / Dimension	Manufacturer Part Number	ECNR300
Beaking Capacity @ Rated Voltage  Electrical, Specialty Fuses  Cartridge, Non-Standard  ECNR  EUNR  Fuse Type  Cartridge  Current Rating  300A  Voltage Rating - AC  250V  Voltage Rating - DC  250V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  Electrical, Specialty Fuses  ECNR  Eartridge  Cartridge  Cartridge, Non-Standard  Size / Dimension  Electrical, Industrial  Electrical, I	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesECNRFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.380" Dia x 8.630" L (60.45mm x 219.20mm)	Category	Circuit Protection
SeriesECNRFuse TypeCartridgeCurrent Rating300AVoltage Rating - AC250VVoltage Rating - DC250VResponse TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension2.380" Dia x 8.630" L (60.45mm x 219.20mm)		Electrical, Specialty Fuses
Fuse Type Current Rating 300A Voltage Rating - AC 250V Voltage Rating - DC 250V Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge Cartridge, Non-Standard Size / Dimension CE, CSA, UL (60.45mm x 219.20mm)	Package	Cartridge, Non-Standard
Current Rating  Voltage Rating - AC  250V  Voltage Rating - DC  250V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  300A  250V  250V  250V  Response Time  Slow  Clectrical, Industrial  Electrical, Industrial  Electrical, Industrial  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  COPERATION OF TABLE OF THE O	Series	ECNR
Voltage Rating - AC  Voltage Rating - DC  250V  Response Time  Slow  Applications  Electrical, Industrial  Features  - Class  RK5  Approvals  CE, CSA, UL  Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Size / Dimension  250V  250V  250V  250V  250V  250V  2600  Electrical, Industrial  CE, CSA, UL  CE, CSA, UL  CE, CSA, UL  COE, CSA, UL  COPERATION CONTRACTOR CONTRAC	Fuse Type	Cartridge
Voltage Rating - DC  Response Time Slow Applications Electrical, Industrial  Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension  250V 250V 260V Slow Slow Slow Slow Approvals - CE, CSA, UL CE, CSA, UL CE, CSA, UL CE, CSA, UL COPIC CE, CSA, UL COPIC CE, CSA, UL COPIC CE, CSA, UL	Current Rating	300A
Response Time Applications Electrical, Industrial  Features - Class RK5 Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Slow Electrical, Industrial - CE, CSA, UL - CE, C	Voltage Rating - AC	250V
Applications Electrical, Industrial  Features - Class RK5  Approvals CE, CSA, UL  Operating Temperature - Breaking Capacity @ Rated Voltage 200kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard Size / Dimension 2.380" Dia x 8.630" L (60.45mm x 219.20mm)	Voltage Rating - DC	250V
Features - Class RK5  Approvals CE, CSA, UL  Operating Temperature - Country @ Rated Voltage 200kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 2.380" Dia x 8.630" L (60.45mm x 219.20mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 2.380" Dia x 8.630" L (60.45mm x 219.20mm)	Applications	Electrical, Industrial
Approvals  CE, CSA, UL  Operating Temperature	Features	-
Operating Temperature  Breaking Capacity @ Rated Voltage  Mounting Type  Holder  Package / Case  Cartridge, Non-Standard  Size / Dimension  2.380" Dia x 8.630" L (60.45mm x 219.20mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA  Mounting Type Holder  Package / Case Cartridge, Non-Standard  Size / Dimension 2.380" Dia x 8.630" L (60.45mm x 219.20mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 2.380" Dia x 8.630" L (60.45mm x 219.20mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 2.380" Dia x 8.630" L (60.45mm x 219.20mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 2.380" Dia x 8.630" L (60.45mm x 219.20mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	2.380" Dia x 8.630" L (60.45mm x 219.20mm)
		Report errors?

### **ECNR300 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ECNR300 Payment Methods**





















### **ECNR300 Shipping Methods**













If you have any question about ECNR300, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com