

ECNR75

ECNR75 Information



Part Number	ECNR75	
Manufacturer	Eaton	
Category	Circuit Protection Electrical, Specialty Fuses	
Description	FUSE RK5 250V TIME-DELAY	
Package	Cylindrical, Blade Terminals	
	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	



Request a Quote

For Reference Only

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECNR75 Specifications

ManufacturerEatonCategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade TerminalsPackageCorrentSteriesCartridgeFuse TypeCartridgeCurrent Rating75AVoltage Rating - ACSiovVoltage Rating - DCSiovApplicationsElectrical, IndustrialFeatures-ClassCircuit AutonomApprovalsCircuit AutonomOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolder TerminalsPackage / CaseSynowalsPackage / Ca		
CategoryCircuit ProtectionElectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesECNRFuse TypeCartridgeCurrent Rating75AVoltage Rating - AC250VVoltage Rating - DCSiowApplicationsElectrical, IndustrialFeatures-ClassK55ApprovalsCE, CSA, ULOperating Temperature200kABreaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseSignificial, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Manufacturer Part Number	ECNR75
Electrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesECNRFuse TypeCartridgeCurrent Rating75AVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature200kABreaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Manufacturer	Eaton
PackageCylindrical, Blade TerminalsSeriesECNRFuse TypeCartridgeCurrent Rating75AVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Type-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Category	Circuit Protection
SeriesCNRFuse TypeCartridgeCurrent Rating75AVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating75AVoltage Rating - AC250VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / Case1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Package	Cylindrical, Blade Terminals
Current Rating75ACurrent Rating - AC250VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Series	ECNR
Voltage Rating - AC250VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Fuse Type	Cartridge
Voltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Current Rating	75A
Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Voltage Rating - AC	250V
ApplicationsElectrical, IndustrialApplications-Features-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Voltage Rating - DC	-
Features-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Response Time	Slow
ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Applications	Electrical, Industrial
ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Features	-
Operating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Class	RK5
Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Approvals	CE, CSA, UL
Mounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Operating Temperature	-
Package / CaseCylindrical, Blade TerminalsSize / Dimension1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.060" Dia x 5.88" W (26.92mm x 149.35mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	1.060" Dia x 5.88" W (26.92mm x 149.35mm)
		Report errors?

ECNR75 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.



If you have any question about ECNR75, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com