

ECP-U1C684MA5

ECP-U1C684MA5 Information

white helsener com	 ECP-U1C684MA5 Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 0.68UF 20% 16VDC 1206 1206 (3216 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECP-U1C684MA5 Specifications

Manufacturer Panasonic Electronic Components Category Capacitors Film Capacitors Film Capacitors Package 1206 (3216 Metric) Series ECP-U(A) Capacitance 0.68µF Tolerance ±20% Voltage Rating - DC 16V Dielectric Material Acrylic, Metallized - Stacked ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Size / Dimension 0.126° L x 0.063° W (3.20mm x 1.60mm) Height - Seated (Max) 0.063″ (1.60mm) Termination Solder Pads Lead Spacing - Applications EMI, RFI Suppression Features Low ESR		
CategoryCapacitorsFilm CapacitorsPackage1206 (3216 Metric)SeriesECP-U(A)Capacitance0.68µFTolerance±20%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialAcrylic, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 85°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.063" (1.60mm)TerminationSolder PadsLead Spacing-FeaturesEMI, RFI SuppressionFeaturesLow ESR	Manufacturer Part Number	ECP-U1C684MA5
Film CapacitorsPackage1206 (3216 Metric)SeriesECP-U(A)Capacitance0.68µFTolerance±20%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialAcrylic, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 85°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.063" (1.60mm)TerminationSolder PadsLead Spacing-FaturesEMI, RFI Suppression	Manufacturer	Panasonic Electronic Components
Package1206 (3216 Metric)SeriesECP-U(A)Capacitance0.68µFTolerance±20%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialAcrylic, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.063" (1.60mm)TerminationSolder PadsLead Spacing-ApplicationsEMI, RFI SuppressionFeaturesLow ESR	Category	Capacitors
Series ECP-U(A) Capacitance 0.68µF Tolerance ±20% Voltage Rating - AC - Voltage Rating - DC 16V Dielectric Material Acrylic, Metallized - Stacked ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 85°C Mounting Type Surface Mount Package / Case 1206 (3216 Metric) Size / Dimension 0.063" (1.60mm) x 1.60mm) Height - Seated (Max) 0.063" (1.60mm) Termination Solder Pads Lead Spacing - Applications EMI, RFI Suppression Features Low ESR		Film Capacitors
Capacitance0.68µFTolerance±20%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialAcrylic, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)Solder PadsLead Spacing-ApplicationsEMI, RFI SuppressionFeaturesLow ESR	Package	1206 (3216 Metric)
±20%Tolerance±20%Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialAcrylic, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.063" (1.60mm)TerminationSolder PadsLead Spacing-ApplicationsEMI, RFI SuppressionKeaturesLow ESR	Series	ECP-U(A)
Voltage Rating - AC-Voltage Rating - DC16VDielectric MaterialAcrylic, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.063" (1.60mm)TerminationSolder PadsLead Spacing-ApplicationsEMI, RFI SuppressionFeaturesLow ESR	Capacitance	0.68µF
Voltage Rating - DC16VDielectric MaterialAcrylic, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.063" (1.60mm)TerminationSolder PadsLead Spacing-ApplicationsEMI, RFI SuppressionFeaturesLow ESR	Tolerance	±20%
Dielectric MaterialAcrylic, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.063" (1.60mm)TerminationSolder PadsLead Spacing-ApplicationsEMI, RFI SuppressionFeaturesLow ESR	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.063" (1.60mm)TerminationSolder PadsLead Spacing-ApplicationsEMI, RFI SuppressionFeaturesLow ESR	Voltage Rating - DC	16V
Operating Temperature-40°C ~ 85°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.063" (1.60mm)TerminationSolder PadsLead Spacing-ApplicationsEMI, RFI SuppressionFeaturesLow ESR	Dielectric Material	Acrylic, Metallized - Stacked
Nounting TypeSurface MountMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.063" (1.60mm)TerminationSolder PadsLead Spacing-ApplicationsEMI, RFI SuppressionFeaturesLow ESR	ESR (Equivalent Series Resistance)	-
Package / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.063" (1.60mm)TerminationSolder PadsLead Spacing-ApplicationsEMI, RFI SuppressionFeaturesLow ESR	Operating Temperature	-40°C ~ 85°C
Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.063" (1.60mm)TerminationSolder PadsLead Spacing-ApplicationsEMI, RFI SuppressionFeaturesLow ESR	Mounting Type	Surface Mount
Height - Seated (Max)0.063" (1.60mm)TerminationSolder PadsLead Spacing-ApplicationsEMI, RFI SuppressionFeaturesLow ESR	Package / Case	1206 (3216 Metric)
TerminationSolder PadsLead Spacing-ApplicationsEMI, RFI SuppressionFeaturesLow ESR	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)
Lead Spacing - Applications EMI, RFI Suppression Features Low ESR	Height - Seated (Max)	0.063" (1.60mm)
ApplicationsEMI, RFI SuppressionFeaturesLow ESR	Termination	Solder Pads
Features Low ESR	Lead Spacing	-
	Applications	EMI, RFI Suppression
Report errors?	Features	Low ESR
		Report errors?

ECP-U1C684MA5 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECP-U1C684MA5 Payment Methods



ECP-U1C684MA5 Shipping Methods



If you have any question about ECP-U1C684MA5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com