



ECP180PS15 Information

Part Number ECP180PS15

Manufacturer XP Power

Category Power Supplie

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 15V 120W

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com

Request a Quote



Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECP180PS15 Specifications

Manufacturer Part Number ECP180PS15 Manufacturer XP Power Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ECP Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ECP Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Manufacturer Part Number	ECP180PS15
Package - Series ECP Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Manufacturer	XP Power
Package - Series ECP Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Category	Power Supplies - External/Internal (Off-Board)
Series ECP Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 15V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 8A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Series	ECP
Voltage - Input85 ~ 264 VACVoltage - Output 115VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)8APower (Watts)120W (180W Forced Air)ApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency92%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Туре	Open Frame
Voltage - Output 2 Voltage - Output 3 Voltage - Output 4 Current - Output (Max) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature Features Adjustable Output, Universal Input Mounting Type Size / Dimension 15V 15V 15V 15V 15V 15V 15V 15	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 Current - Output (Max) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Mounting Type Chassis Mount Size / Dimension	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension - Output (Max) - Adjustable Output, Universal Input Adjustable Output, Universal Input 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Voltage - Output 1	15V
Voltage - Output 4 Current - Output (Max) 8A Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension -00°L x 2.00° W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 120W (180W Forced Air) 4kV (4000V) 6ut (180W Forced Air) 4kV (4000V) 6ut (180W Forced Air) 4kV (4000V) 6ut (180W Forced Air) 6ut	Voltage - Output 4	-
Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Current - Output (Max)	8A
Voltage - Isolation 4kV (4000V) Efficiency 92% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Power (Watts)	120W (180W Forced Air)
Efficiency 92% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Applications	ITE (Commercial), Medical
Operating Temperature -20°C ~ 70°C (With Derating) Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Voltage - Isolation	4kV (4000V)
Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Efficiency	92%
Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Operating Temperature	-20°C ~ 70°C (With Derating)
Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Features	Adjustable Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)
		Report errors?

ECP180PS15 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECP180PS15 Payment Methods



















ECP180PS15 Shipping Methods













If you have any question about ECP180PS15, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com