



ECP180PS28 Information

Part Number ECP180PS28 Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 28V 120W

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECP180PS28 Specifications

Manufacturer Part Number ECP180PS28 Manufacturer XP Power Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ECP Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.43A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 93% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm) Report errors?		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ECP Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.43A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 93% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Manufacturer Part Number	ECP180PS28
Package - Series ECP Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.43A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 93% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Manufacturer	XP Power
Package - Series ECP Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.43A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 93% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Category	Power Supplies - External/Internal (Off-Board)
Series ECP Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.43A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 93% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.43A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 93% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 28V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 6.43A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 93% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Series	ECP
Voltage - Input85 ~ 264 VACVoltage - Output 128VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)6.43APower (Watts)120W (180W Forced Air)ApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency93%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Туре	Open Frame
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 28V A 28V 28V Chassis Mount -20°C ~ 70°C (With Denating) Chassis Mount 4kV (4000V) Chassis Mount 4kV (4000V) Chassis Mount 4kV (4000V) Chassis Mount 4kV (4000V) Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 Current - Output (Max) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature Features Adjustable Output, Universal Input Mounting Type Size / Dimension - Output 2 - Current - Output (Max) - Current - Output (New York Air) - Current - Output (New York Air) - Current - Output (Max) - Current - Output (New York Air) - Current - Output (Max) - Current - Output (New York Air) - Current - Output (Max) - Curre	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension - Output (Max) - Chassis Mount	Voltage - Output 1	28V
Voltage - Output 4 Current - Output (Max) 6.43A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 93% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Voltage - Output 2	-
Current - Output (Max) 6.43A Power (Watts) 120W (180W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 93% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 93% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 120W (180W Forced Air) 4kV (4000V) 6ut	Voltage - Output 4	-
Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 93% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Current - Output (Max)	6.43A
Voltage - Isolation 4kV (4000V) Efficiency 93% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Power (Watts)	120W (180W Forced Air)
Efficiency 93% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Applications	ITE (Commercial), Medical
Operating Temperature -20°C ~ 70°C (With Derating) Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Voltage - Isolation	4kV (4000V)
Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Efficiency	93%
Mounting Type Chassis Mount Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Operating Temperature	-20°C ~ 70°C (With Derating)
Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Features	Adjustable Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)
		Report errors?

ECP180PS28 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECP180PS28 Payment Methods



















ECP180PS28 Shipping Methods













If you have any question about ECP180PS28, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com