



## **ECP180PS28 Information**

ner.day

For Reference Only

Part Number ECP180PS28
Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

**Description** AC/DC CONVERTER 28V 120W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **ECP180PS28 Specifications**

Manufacturer Part Number         ECP180PS28           Manufacturer         XP Power           Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         ECP           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         28V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.43A           Power (Watts)         120W (180W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         93%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)           Report errors?		
Category         Power Supplies - External/Internal (Off-Board)           AC DC Converters           Package         -           Series         ECP           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         28V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.43A           Power (Watts)         120W (180W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         93%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Manufacturer Part Number	ECP180PS28
Package         -           Series         ECP           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         28V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.43A           Power (Watts)         120W (180W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         93%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Manufacturer	XP Power
Package         -           Series         ECP           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         28V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.43A           Power (Watts)         120W (180W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         93%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Category	Power Supplies - External/Internal (Off-Board)
Series         ECP           Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         28V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.43A           Power (Watts)         120W (180W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         93%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)		AC DC Converters
Type         Open Frame           Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         28V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.43A           Power (Watts)         120W (180W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         93%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Package	-
Number of Outputs         1           Voltage - Input         85 ~ 264 VAC           Voltage - Output 1         28V           Voltage - Output 2         -           Voltage - Output 3         -           Voltage - Output 4         -           Current - Output (Max)         6.43A           Power (Watts)         120W (180W Forced Air)           Applications         ITE (Commercial), Medical           Voltage - Isolation         4kV (4000V)           Efficiency         93%           Operating Temperature         -20°C ~ 70°C (With Derating)           Features         Adjustable Output, Universal Input           Mounting Type         Chassis Mount           Size / Dimension         4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Series	ECP
Voltage - Input85 ~ 264 VACVoltage - Output 128VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)6.43APower (Watts)120W (180W Forced Air)ApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency93%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Туре	Open Frame
Voltage - Output 1  Voltage - Output 2  - Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Power (Watts)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  28V  A  28V  28V  Chassis Mount  -20°C ~ 70°C (With Denating)  Chassis Mount  4kV (4000V)  Chassis Mount  4kV (4000V)  Chassis Mount  4kV (4000V)  Chassis Mount  4kV (4000V)  Chassis Mount  Size / Dimension  4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Number of Outputs	1
Voltage - Output 2  Voltage - Output 3  - Voltage - Output 4  Current - Output (Max)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  Features  Adjustable Output, Universal Input  Mounting Type  Size / Dimension  - Output 2  - Current - Output (Max)  - Current - Output (New York Air)  - Current - Output (New York Air)  - Current - Output (Max)  - Current - Output (New York Air)  - Current - Output (Max)  - Current - Output (New York Air)  - Current - Output (Max)  - Curre	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3  Voltage - Output 4  - Current - Output (Max)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  - Output (Max)  - Chassis Mount	Voltage - Output 1	28V
Voltage - Output 4  Current - Output (Max)  6.43A  Power (Watts)  120W (180W Forced Air)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  93%  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Voltage - Output 2	-
Current - Output (Max)  6.43A  Power (Watts)  120W (180W Forced Air)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  93%  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Voltage - Output 3	-
Power (Watts)  Applications  ITE (Commercial), Medical  Voltage - Isolation  4kV (4000V)  Efficiency  93%  Operating Temperature  -20°C ~ 70°C (With Derating)  Features  Adjustable Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  120W (180W Forced Air)  4kV (4000V)  6ut	Voltage - Output 4	-
Applications ITE (Commercial), Medical  Voltage - Isolation 4kV (4000V)  Efficiency 93%  Operating Temperature -20°C ~ 70°C (With Derating)  Features Adjustable Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Current - Output (Max)	6.43A
Voltage - Isolation 4kV (4000V)  Efficiency 93%  Operating Temperature -20°C ~ 70°C (With Derating)  Features Adjustable Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Power (Watts)	120W (180W Forced Air)
Efficiency 93%  Operating Temperature -20°C ~ 70°C (With Derating)  Features Adjustable Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Applications	ITE (Commercial), Medical
Operating Temperature  -20°C ~ 70°C (With Derating)  Adjustable Output, Universal Input  Mounting Type  Chassis Mount  Size / Dimension  4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Voltage - Isolation	4kV (4000V)
Features Adjustable Output, Universal Input  Mounting Type Chassis Mount  Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Efficiency	93%
Mounting Type Chassis Mount  Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Operating Temperature	-20°C ~ 70°C (With Derating)
Size / Dimension 4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)	Features	Adjustable Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	4.00" L x 2.00" W x 0.84" H (101.6mm x 50.8mm x 21.6mm)
		Report errors?

#### **ECP180PS28 Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ECP180PS28 Payment Methods**



















## **ECP180PS28 Shipping Methods**













If you have any question about ECP180PS28, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com