



ECP225PS48 Information

Part Number ECP225PS48
Manufacturer XP Power

Category Power Supplies - External/Internal (Off-Board)

AC DC Converters

Description AC/DC CONVERTER 48V 150W

Package -

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECP225PS48 Specifications

Manufacturer Part Number ECP225P848 Manufacturer XP Power Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ECP Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.69A Power (Watts) 150W (225W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)		
Category Power Supplies - External/Internal (Off-Board) AC DC Converters Package - Series ECP Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.69A Power (Watts) 150W (225W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Manufacturer Part Number	ECP225PS48
Package - Series ECP Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.69A Power (Watts) 150W (225W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Manufacturer	XP Power
Package - Series ECP Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.69A Power (Watts) 150W (225W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Category	Power Supplies - External/Internal (Off-Board)
Series ECP Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.69A Power (Watts) 150W (225W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)		AC DC Converters
Type Open Frame Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.69A Power (Watts) 150W (225W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Package	-
Number of Outputs 1 Voltage - Input 85 ~ 264 VAC Voltage - Output 1 48V Voltage - Output 2 - Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) 4.69A Power (Watts) 150W (225W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Series	ECP
Voltage - Input85 ~ 264 VACVoltage - Output 148VVoltage - Output 2-Voltage - Output 3-Voltage - Output 4-Current - Output (Max)4.69APower (Watts)150W (225W Forced Air)ApplicationsITE (Commercial), MedicalVoltage - Isolation4kV (4000V)Efficiency94%Operating Temperature-20°C ~ 70°C (With Derating)FeaturesAdjustable Output, Universal InputMounting TypeChassis MountSize / Dimension5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Туре	Open Frame
Voltage - Output 1 Voltage - Output 2 - Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 48V	Number of Outputs	1
Voltage - Output 2 Voltage - Output 3 - Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension -00°L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Voltage - Input	85 ~ 264 VAC
Voltage - Output 3 Voltage - Output 4 - Current - Output (Max) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension - Output (Max) - Chassis Mount	Voltage - Output 1	48V
Voltage - Output 4 Current - Output (Max) Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension -20°L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Voltage - Output 2	-
Current - Output (Max) Power (Watts) 150W (225W Forced Air) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 4.69A 150W (225W Forced Air) ITE (Commercial), Medical 4kV (4000V) 64kV (4000V) 94% Chassis Mount 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Voltage - Output 3	-
Power (Watts) Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 150W (225W Forced Air) Akly (4000V) 64kV (4000V) Coperating Temperature -20°C ~ 70°C (With Derating) Adjustable Output, Universal Input Chassis Mount 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Voltage - Output 4	-
Applications ITE (Commercial), Medical Voltage - Isolation 4kV (4000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Current - Output (Max)	4.69A
Voltage - Isolation 4kV (4000V) Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Power (Watts)	150W (225W Forced Air)
Efficiency 94% Operating Temperature -20°C ~ 70°C (With Derating) Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Applications	ITE (Commercial), Medical
Operating Temperature -20°C ~ 70°C (With Derating) Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Voltage - Isolation	4kV (4000V)
Features Adjustable Output, Universal Input Mounting Type Chassis Mount Size / Dimension 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Efficiency	94%
Mounting Type Chassis Mount Size / Dimension 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Operating Temperature	-20°C ~ 70°C (With Derating)
Size / Dimension 5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)	Features	Adjustable Output, Universal Input
	Mounting Type	Chassis Mount
Report errors?	Size / Dimension	5.00" L x 2.50" W x 1.00" H (127.0mm x 63.5mm x 25.4mm)
		Report errors?

ECP225PS48 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECP225PS48 Payment Methods



















ECP225PS48 Shipping Methods













If you have any question about ECP225PS48, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com