



ECQ-E10103RJF Information

Heisener.com

Part Number ECQ-E10103RJF

Manufacturer Panasonic Electronic Components

Category Capacitors

Film Capacitors

Description CAP FILM 10000PF 5% 1KVDC RADIAL

Package Radia

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECQ-E10103RJF Specifications

Manufacturer Part Number ECQ-E10103RJF Manufacturer Panasonic Electronic Components Category Capacitors Film Capacitors Package Radial Series ECQ-E(F) Capacitance 10000pF Tolerance ±5% Voltage Rating - AC 125V Voltage Rating - DC 1000V (1kV) Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.610" L x 0.236" W (15.50mm x 6.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	•	
Category Capacitors Film Capacitors Package Radial Series ECQ-E(F) Capacitance 10000pF Tolerance ±5% Voltage Rating - AC 125V Voltage Rating - DC 1000V (1kV) Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.610" L x 0.236" W (15.50mm x 6.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Manufacturer Part Number	ECQ-E10103RJF
Package Radial Series ECQ-E(F) Capacitance 10000pF Tolerance ±5% Voltage Rating - AC 125V Voltage Rating - DC 1000V (1kV) Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.610" L x 0.236" W (15.50mm x 6.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECQ-E(F)Capacitance10000pFTolerance±5%Voltage Rating - AC125VVoltage Rating - DC1000V (1kV)Dielectric MaterialPolyester, MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.610" L x 0.236" W (15.50mm x 6.00mm)Height - Seated (Max)0.630" (16.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Category	Capacitors
Series ECQ-E(F) Capacitance 10000pF Tolerance ±5% Voltage Rating - AC 125V Voltage Rating - DC 1000V (1kV) Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.610" L x 0.236" W (15.50mm x 6.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -		Film Capacitors
Capacitance 10000pF Tolerance ±5% Voltage Rating - AC 125V Voltage Rating - DC 1000V (1kV) Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.610" L x 0.236" W (15.50mm x 6.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Package	Radial
Tolerance ±5% Voltage Rating - AC 125V Voltage Rating - DC 1000V (1kV) Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.610" L x 0.236" W (15.50mm x 6.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Series	ECQ-E(F)
Voltage Rating - AC Voltage Rating - DC 1000V (1kV) Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.610" L x 0.236" W (15.50mm x 6.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features	Capacitance	10000pF
Voltage Rating - DC Dielectric Material Polyester, Metallized ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.610" L x 0.236" W (15.50mm x 6.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Tolerance	±5%
Dielectric Material ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.610" L x 0.236" W (15.50mm x 6.00mm) Height - Seated (Max) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Voltage Rating - AC	125V
ESR (Equivalent Series Resistance) Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.610" L x 0.236" W (15.50mm x 6.00mm) Height - Seated (Max) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features	Voltage Rating - DC	1000V (1kV)
Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.610" L x 0.236" W (15.50mm x 6.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features	Dielectric Material	Polyester, Metallized
Mounting Type Package / Case Radial Size / Dimension 0.610" L x 0.236" W (15.50mm x 6.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	ESR (Equivalent Series Resistance)	-
Package / Case Radial Size / Dimension 0.610" L x 0.236" W (15.50mm x 6.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Operating Temperature	-40°C ~ 105°C
Size / Dimension 0.610" L x 0.236" W (15.50mm x 6.00mm) Height - Seated (Max) 0.630" (16.00mm) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Mounting Type	Through Hole
Height - Seated (Max) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Package / Case	Radial
Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications General Purpose Features -	Size / Dimension	0.610" L x 0.236" W (15.50mm x 6.00mm)
Lead Spacing0.295" (7.50mm)ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.630" (16.00mm)
Applications General Purpose Features -	Termination	PC Pins
Features -	Lead Spacing	0.295" (7.50mm)
	Applications	General Purpose
Report errors?	Features	-
		Report errors?

ECQ-E10103RJF Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECQ-E10103RJF Payment Methods



















ECQ-E10103RJF Shipping Methods













If you have any question about ECQ-E10103RJF, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com