

ECQ-V1104JM2

ECQ-V1104JM2 Information

www.heisener.com	Part Number Manufacturer Category Description Package	Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 0.1UF 5% 100VDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECQ-V1104JM2 Specifications

Anufacturer Panasonic Electronic Components Category Capacitors Film Capacitors Film Capacitors Package Radial Series ECQ-V Capacitance 0.1µF Tolerance ±5% Voltage Rating - AC - Voltage Rating - DC 100V Dielectric Material Polyester, Metallized - Stacked Strigg Temperature - Operating Temperature - Package / Case Radial Size / Dimension 0.295" L x 0.17" W (7.50mm x 4.50mm) Height - Seated (Max) 0.315" (8.00mm) Termination PC Pins Lead Spacing - Applications General Purpose Features -		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesECQ-VCapacitance0.1µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC100VDielectric MaterialPolyester, Metallized - StackedSeries Resistance)-Operating Temperature-40°C ~ 105°CMouning TypeRadialSize / Dimension0.295° L x 0.177° W (7.50mm x 4.50mm)Height - Seated (Max)0.315" (8.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Manufacturer Part Number	ECQ-V1104JM2
Fin CapacitorsPackageRadialSeriesECQ-VCapacitance0.1µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC100VDielectric MaterialPolyester, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.177" W (7.50mm x 4.50mm)Height - Seated (Max)0.315" (8.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECQ-VCapacitance0.1µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC100VDielectric MaterialPolyester, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295° L x 0.177° W (7.50mm x 4.50mm)Height - Seated (Max)0.315° (8.00mm)Lead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Category	Capacitors
Series ECQ-V Capacitance 0.1µF Tolerance ±5% Voltage Rating - AC - Voltage Rating - DC 100V Dielectric Material Polyester, Metallized - Stacked ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dinension 0.295° L x 0.177° W (7.50mm x 4.50mm) Height - Seated (Max) 0.315" (8.00mm) Lead Spacing 0.197" (5.00mm) Applications General Purpose Features -		Film Capacitors
Capacitance0.1µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC100VDielectric MaterialPolyester, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.295" L x 0.177" W (7.50mm x 4.50mm)Height - Seated (Max)0.315" (8.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC100VDielectric MaterialPolyester, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.177" W (7.50mm x 4.50mm)Height - Seated (Max)0.315" (8.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Series	ECQ-V
Voltage Rating - AC-Voltage Rating - DC100VDielectric MaterialPolyester, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.177" W (7.50mm x 4.50mm)Height - Seated (Max)0.315" (8.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Capacitance	0.1µF
Voltage Rating - DC100VDielectric MaterialPolyester, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.177" W (7.50mm x 4.50mm)Height - Seated (Max)0.315" (8.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolyester, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.177" W (7.50mm x 4.50mm)Height - Seated (Max)0.315" (8.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.177" W (7.50mm x 4.50mm)Height - Seated (Max)0.315" (8.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	100V
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.177" W (7.50mm x 4.50mm)Height - Seated (Max)0.315" (8.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyester, Metallized - Stacked
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.295" L x 0.177" W (7.50mm x 4.50mm)Height - Seated (Max)0.315" (8.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.295" L x 0.177" W (7.50mm x 4.50mm)Height - Seated (Max)0.315" (8.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Operating Temperature	$-40^{\circ}C \sim 105^{\circ}C$
Size / Dimension0.295" L x 0.177" W (7.50mm x 4.50mm)Height - Seated (Max)0.315" (8.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.315" (8.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.295" L x 0.177" W (7.50mm x 4.50mm)
Lead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.315" (8.00mm)
ApplicationsGeneral PurposeFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.197" (5.00mm)
	Applications	General Purpose
Report errors?	Features	-
hepottenois.		Report errors?

ECQ-V1104JM2 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECQ-V1104JM2 Payment Methods



ECQ-V1104JM2 Shipping Methods



If you have any question about ECQ-V1104JM2, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com