

ECQ-V1H273JL2

a Quote

ECQ-V1H273JL2 Information

Heisener.com	Part Number	ECQ-V1H273JL2	
	Manufacturer	Panasonic Electronic Components	_ ■2
	Category	Capacitors Film Capacitors	ēr
	Description	CAP FILM 0.027UF 5% 50VDC RADIAL	- 54
	Package	Radial	
		For the pricing/inventory/lead time, please contact	⋳⋿⋓⋼
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Reque

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECQ-V1H273JL2 Specifications

Manufacturer Panasonic Electronic Components Category Capacitors Film Capacitors Film Capacitors Package Radial Series ECQ-V Capacitance 0.027µF Tolerance ±5% Voltage Rating - AC - Voltage Rating - DC 50V Dielectric Material Polyester, Metallized - Stacked Strigg Temperature - Operating Temperature 40°C ~ 105°C Mounting Type Through Hole Size / Dimension 0.280" (6.00mm) Height - Seated (Max) 0.236" (6.00mm) Termination PC Pins Lead Spacing General Purpose		
Category Capacitors Film Capacitors Package Radial Series ECQ-V Capacitance 0.027µF Tolerance ±5% Voltage Rating - AC - Voltage Rating - DC 50V Dielectric Material Polyester, Metallized - Stacked Operating Temperature - Voltage / Case Radial Size / Dimension 0.280" L x 0.126" W (7.30mm x 3.20mm) Height - Seated (Max) 0.236" (6.00mm) Termination PC Pins Lead Spacing 0.197" (5.00mm) Applications General Purpose Features -	Manufacturer Part Number	ECQ-V1H273JL2
Fin CapacitorsPackageRadialSeriesECQ-VCapacitance0.027μFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.236" (6.00mm)Height - Seated (Max)0.236" (6.00mm)ApplicationsGeneral PurposeFeatures-	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECQ-VCapacitance0.027µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.236" (6.00mm)Height - Seated (Max)0.236" (5.00mm)Lead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Category	Capacitors
Series ECQ-V Capacitance 0.027μF Tolerance ±5% Voltage Rating - AC - Voltage Rating - DC 50V Dielectric Material Polyester, Metallized - Stacked ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.287" L x 0.126" W (7.30mm x 3.20mm) Height - Seated (Max) 0.236" (6.00mm) Termination PC Pins Lead Spacing 0.197" (5.00mm) Applications General Purpose Features -		Film Capacitors
Capacitance0.027μFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.287" L x 0.126" W (7.30mm x 3.20mm)Height - Seated (Max)0.236" (6.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.287" L x 0.126" W (7.30mm x 3.20mm)Height - Seated (Max)0.236" (6.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Series	ECQ-V
NoticeInterferenceVoltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.287" L x 0.126" W (7.30mm x 3.20mm)Height - Seated (Max)0.236" (6.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Capacitance	0.027µF
Voltage Rating - DC50VDielectric MaterialPolyester, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.287" L x 0.126" W (7.30mm x 3.20mm)Height - Seated (Max)0.236" (6.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Tolerance	±5%
Dielectric MaterialPolyester, Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.287" L x 0.126" W (7.30mm x 3.20mm)Height - Seated (Max)0.236" (6.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.287" L x 0.126" W (7.30mm x 3.20mm)Height - Seated (Max)0.236" (6.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	50V
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.287" L x 0.126" W (7.30mm x 3.20mm)Height - Seated (Max)0.236" (6.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyester, Metallized - Stacked
Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.287" L x 0.126" W (7.30mm x 3.20mm)Height - Seated (Max)0.236" (6.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.287" L x 0.126" W (7.30mm x 3.20mm)Height - Seated (Max)0.236" (6.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Operating Temperature	-40°C ~ 105°C
Size / Dimension 0.287" L x 0.126" W (7.30mm x 3.20mm) Height - Seated (Max) 0.236" (6.00mm) Termination PC Pins Lead Spacing 0.197" (5.00mm) Applications General Purpose Features -	Mounting Type	Through Hole
Height - Seated (Max)0.236" (6.00mm)TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Size / Dimension	0.287" L x 0.126" W (7.30mm x 3.20mm)
Lead Spacing0.197" (5.00mm)ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.236" (6.00mm)
ApplicationsGeneral PurposeFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.197" (5.00mm)
	Applications	General Purpose
Report errors?	Features	-
		Report errors?

ECQ-V1H273JL2 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECQ-V1H273JL2 Payment Methods



ECQ-V1H273JL2 Shipping Methods



If you have any question about ECQ-V1H273JL2, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com