



### **ECS-P83-ANX Information**



For Reference Only

Part Number ECS-P83-ANX Manufacturer ECS Inc.

Category Crystals, Oscillators, Resonators

**Programmable Oscillators** 

**Description**OSC PROG HCMOS 3.3V EN/DS TH**Package**8-DIP, 4 Leads (Half Size, Metal Can)

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **ECS-P83-ANX Specifications**

Manufacturer Part Number         ECS-P83-ANX           Manufacturer         ECS Inc.           Category         Crystals, Oscillators, Resonators           Package         8-DIP, 4 Leads (Half Size, Metal Can)           Series         ECS-P83X           Type         XO (Standard)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 150MHz           Function         Enable/Disable           Output         HCMOS           Voltage - Supply         3.3V           Frequency Stability         -           Frequency Stability (Total)         ±100ppm           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         28mA           Ratings         -           Mounting Type         Through Hole           Package / Case         8-DIP, 4 Leads (Half Size, Metal Can)           Size / Dimension         0.520" L x 0.520" W (13.20mm x 13.20mm)           Height         0.213" (5.40mm)		
Category         Crystals, Oscillators, Resonators           Package         8-DIP, 4 Leads (Half Size, Metal Can)           Series         ECS-P83X           Type         XO (Standard)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 150MHz           Function         Enable/Disable           Output         HCMOS           Voltage - Supply         3.3V           Frequency Stability         -           Frequency Stability (Total)         ±100ppm           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         28mA           Ratings         -           Mounting Type         Through Hole           Package / Case         8-DIP, 4 Leads (Half Size, Metal Can)           Size / Dimension         0.520" Lx 0.520" W (13.20mm x 13.20mm)           Height         0.213" (5.40mm)	Manufacturer Part Number	ECS-P83-ANX
Package 8-DIP, 4 Leads (Half Size, Metal Can) Series ECS-P83X Type XO (Standard) Programmable Type Programmed as Request Available Frequency Range IMHz ~ 150MHz Function Enable/Disable Output HCMOS Voltage - Supply 3.3V Frequency Stability Frequency Stability (Total) ±100ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 28mA Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.213" (5.40mm)	Manufacturer	ECS Inc.
Package         8-DIP, 4 Leads (Half Size, Metal Can)           Series         ECS-P83X           Type         XO (Standard)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 150MHz           Function         Enable/Disable           Output         HCMOS           Voltage - Supply         3.3V           Frequency Stability         -           Frequency Stability (Total)         ±100ppm           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         28mA           Ratings         -           Mounting Type         Through Hole           Package / Case         8-DIP, 4 Leads (Half Size, Metal Can)           Size / Dimension         0.520" L x 0.520" W (13.20mm x 13.20mm)           Height         0.213" (5.40mm)	Category	Crystals, Oscillators, Resonators
Series         ECS-P83X           Type         XO (Standard)           Programmable Type         Programmed as Request           Available Frequency Range         1MHz ~ 150MHz           Function         Enable/Disable           Output         HCMOS           Voltage - Supply         3.3V           Frequency Stability         -           Frequency Stability (Total)         ±100ppm           Operating Temperature         -40°C ~ 85°C           Spread Spectrum Bandwidth         -           Current - Supply (Max)         28mA           Ratings         -           Mounting Type         Through Hole           Package / Case         8-DIP, 4 Leads (Half Size, Metal Can)           Size / Dimension         0.520" L x 0.520" W (13.20mm x 13.20mm)           Height         0.213" (5.40mm)		Programmable Oscillators
TypeXO (Standard)Programmable TypeProgrammed as RequestAvailable Frequency Range1MHz ~ 150MHzFunctionEnable/DisableOutputHCMOSVoltage - Supply3.3VFrequency Stability-Frequency Stability (Total)±100ppmOperating Temperature-40°C ~ 85°CSpread Spectrum Bandwidth-Current - Supply (Max)28mARatings-Mounting TypeThrough HolePackage / Case8-DIP, 4 Leads (Half Size, Metal Can)Size / Dimension0.520" L x 0.520" W (13.20mm x 13.20mm)Height0.213" (5.40mm)	Package	8-DIP, 4 Leads (Half Size, Metal Can)
Programmable Type Programmed as Request  Available Frequency Range 1MHz ~ 150MHz  Function Enable/Disable  Output HCMOS  Voltage - Supply 3.3V  Frequency Stability  Frequency Stability (Total) ±100ppm  Operating Temperature 40°C ~ 85°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 28mA  Ratings  Mounting Type Through Hole  Package / Case 8-DIP, 4 Leads (Half Size, Metal Can)  Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm)  Height 0.213" (5.40mm)	Series	ECS-P83X
Available Frequency Range  IMHz ~ 150MHz  Enable/Disable  Output  HCMOS  Voltage - Supply  3.3V  Frequency Stability	Туре	XO (Standard)
Function Enable/Disable Output HCMOS Voltage - Supply 3.3V Frequency Stability - Frequency Stability (Total) ±100ppm Operating Temperature -40°C ~ 85°C Spread Spectrum Bandwidth - Current - Supply (Max) 28mA Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.213" (5.40mm)	Programmable Type	Programmed as Request
Output HCMOS  Voltage - Supply 3.3V  Frequency Stability - Frequency Stability (Total) ±100ppm  Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth - Current - Supply (Max) 28mA  Ratings - Mounting Type Through Hole  Package / Case 8-DIP, 4 Leads (Half Size, Metal Can)  Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm)  Height 0.213" (5.40mm)	Available Frequency Range	1MHz ~ 150MHz
Voltage - Supply  3.3V  Frequency Stability	Function	Enable/Disable
Frequency Stability (Total) ±100ppm  Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 28mA  Ratings -  Mounting Type Through Hole  Package / Case 8-DIP, 4 Leads (Half Size, Metal Can)  Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm)  Height 0.213" (5.40mm)	Output	HCMOS
Frequency Stability (Total) ±100ppm  Operating Temperature -40°C ~ 85°C  Spread Spectrum Bandwidth -  Current - Supply (Max) 28mA  Ratings -  Mounting Type Through Hole  Package / Case 8-DIP, 4 Leads (Half Size, Metal Can)  Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm)  Height 0.213" (5.40mm)	Voltage - Supply	3.3V
Operating Temperature  -40°C ~ 85°C  Spread Spectrum Bandwidth  - Current - Supply (Max)  Ratings  - Mounting Type  Through Hole  Package / Case  8-DIP, 4 Leads (Half Size, Metal Can)  Size / Dimension  0.520" L x 0.520" W (13.20mm x 13.20mm)  Height  0.213" (5.40mm)	Frequency Stability	-
Spread Spectrum Bandwidth  Current - Supply (Max)  Ratings  - Mounting Type  Through Hole  Package / Case  8-DIP, 4 Leads (Half Size, Metal Can)  Size / Dimension  0.520" L x 0.520" W (13.20mm x 13.20mm)  Height  0.213" (5.40mm)	Frequency Stability (Total)	±100ppm
Current - Supply (Max)  Ratings  - Mounting Type  Through Hole  Package / Case  8-DIP, 4 Leads (Half Size, Metal Can)  Size / Dimension  0.520" L x 0.520" W (13.20mm x 13.20mm)  Height  0.213" (5.40mm)	Operating Temperature	-40°C ~ 85°C
Ratings - Mounting Type Through Hole Package / Case 8-DIP, 4 Leads (Half Size, Metal Can) Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm) Height 0.213" (5.40mm)	Spread Spectrum Bandwidth	-
Mounting Type Through Hole  Package / Case 8-DIP, 4 Leads (Half Size, Metal Can)  Size / Dimension 0.520" L x 0.520" W (13.20mm x 13.20mm)  Height 0.213" (5.40mm)	Current - Supply (Max)	28mA
Package / Case         8-DIP, 4 Leads (Half Size, Metal Can)           Size / Dimension         0.520" L x 0.520" W (13.20mm x 13.20mm)           Height         0.213" (5.40mm)	Ratings	-
Size / Dimension       0.520" L x 0.520" W (13.20mm x 13.20mm)         Height       0.213" (5.40mm)	Mounting Type	Through Hole
Height 0.213" (5.40mm)	Package / Case	8-DIP, 4 Leads (Half Size, Metal Can)
	Size / Dimension	0.520" L x 0.520" W (13.20mm x 13.20mm)
Report errors?	Height	0.213" (5.40mm)
		Report errors?

#### **ECS-P83-ANX Guarantees**



#### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ECS-P83-ANX Payment Methods**



















### **ECS-P83-ANX Shipping Methods**













If you have any question about ECS-P83-ANX, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com