

ECSR40 Information

Ma

Heisener.com

Part Number ECSR40
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

Description UL CLASS RK-5 TIME DELAY

Package Cartridge, Non-Standard

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

For Reference Only

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECSR40 Specifications

Manufacturer Part NumberECSR40ManufacturerEatonCategoryCircuit ProtectionPackageCartridge, Non-StandardSeriesECSRFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.50" L (26.92mm x 139.70mm)		
CategoryCircuit Protection Electrical, Specialty FusesPackageCartridge, Non-StandardSeriesECSRFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Manufacturer Part Number	ECSR40
Beckage Cartridge, Non-Standard Series ECSR Fuse Type Cartridge Current Rating 40A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension EECSR ECSR ECSR ECSR ECSR ECSR ECSR ECSR	Manufacturer	Eaton
PackageCartridge, Non-StandardSeriesECSRFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Category	Circuit Protection
SeriesECSRFuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.50" L (26.92mm x 139.70mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating40AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCartridge, Non-StandardSize / Dimension1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Package	Cartridge, Non-Standard
Current Rating Voltage Rating - AC 600V Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 40A 40A 600V 40A 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 600V 60	Series	ECSR
Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Class Color Dia x 5.50" L (26.92mm x 139.70mm)	Current Rating	40A
Response Time Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension Slow Electrical, Industrial - CE, CSA, UL - CE, CSA, U	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Voltage Rating - DC	-
Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Operating Temperature	-
Package / Case Cartridge, Non-Standard Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.060" Dia x 5.50" L (26.92mm x 139.70mm)	Mounting Type	Holder
	Package / Case	Cartridge, Non-Standard
Report errors?	Size / Dimension	1.060" Dia x 5.50" L (26.92mm x 139.70mm)
Report errors.		Report errors?

ECSR40 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECSR40 Payment Methods





















ECSR40 Shipping Methods













If you have any question about ECSR40, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com