

ECSR80 Information

Heisener.com

Part Number ECSR80
Manufacturer Eaton

Category Circuit Protection

Electrical, Specialty Fuses

DescriptionUL CLASS RK-5 TIME DELAYPackageCylindrical, Blade Terminals

For the pricing/inventory/lead time, please contact

us

For Reference Only

Website: https://www.heisener.com
E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









ECSR80 Specifications

Manufacturer Part NumberECSR80ManufacturerEatonCategoryCircuit ProtectionBeckageCylindrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesECSRFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.110" Dia x 7.880" L (28.19mm x 200.15mm)Report errors?		
CategoryCircuit ProtectionPackageCylindrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesECSRFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.110" Dia x 7.880" L (28.19mm x 200.15mm)	Manufacturer Part Number	ECSR80
PackageElectrical, Specialty FusesPackageCylindrical, Blade TerminalsSeriesECSRFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.110" Dia x 7.880" L (28.19mm x 200.15mm)	Manufacturer	Eaton
PackageCylindrical, Blade TerminalsSeriesECSRFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.110" Dia x 7.880" L (28.19mm x 200.15mm)	Category	Circuit Protection
SeriesECSRFuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.110" Dia x 7.880" L (28.19mm x 200.15mm)		Electrical, Specialty Fuses
Fuse TypeCartridgeCurrent Rating80AVoltage Rating - AC600VVoltage Rating - DC-Response TimeSlowApplicationsElectrical, IndustrialFeatures-ClassRK5ApprovalsCE, CSA, ULOperating Temperature-Breaking Capacity @ Rated Voltage200kAMounting TypeHolderPackage / CaseCylindrical, Blade TerminalsSize / Dimension1.110" Dia x 7.880" L (28.19mm x 200.15mm)	Package	Cylindrical, Blade Terminals
Current Rating 80A Voltage Rating - AC 600V Voltage Rating - DC - Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.110" Dia x 7.880" L (28.19mm x 200.15mm)	Series	ECSR
Voltage Rating - AC Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension 600V	Fuse Type	Cartridge
Voltage Rating - DC Response Time Slow Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension - Slow Slow Slow Slow Slow Slow Slow Slow	Current Rating	80A
Response Time Applications Electrical, Industrial Features - Class RK5 Approvals Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Size / Dimension Slow Slow Electrical, Industrial - RK5 AK5 APPOVALS CE, CSA, UL - Breaking Capacity @ Rated Voltage CURLS COBA Holder CURLS CURL	Voltage Rating - AC	600V
Applications Electrical, Industrial Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.110" Dia x 7.880" L (28.19mm x 200.15mm)	Voltage Rating - DC	-
Features - Class RK5 Approvals CE, CSA, UL Operating Temperature - Streaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.110" Dia x 7.880" L (28.19mm x 200.15mm)	Response Time	Slow
Class RK5 Approvals CE, CSA, UL Operating Temperature - Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.110" Dia x 7.880" L (28.19mm x 200.15mm)	Applications	Electrical, Industrial
Approvals CE, CSA, UL Operating Temperature	Features	-
Operating Temperature Breaking Capacity @ Rated Voltage Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.110" Dia x 7.880" L (28.19mm x 200.15mm)	Class	RK5
Breaking Capacity @ Rated Voltage 200kA Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.110" Dia x 7.880" L (28.19mm x 200.15mm)	Approvals	CE, CSA, UL
Mounting Type Holder Package / Case Cylindrical, Blade Terminals Size / Dimension 1.110" Dia x 7.880" L (28.19mm x 200.15mm)	Operating Temperature	-
Package / Case Cylindrical, Blade Terminals Size / Dimension 1.110" Dia x 7.880" L (28.19mm x 200.15mm)	Breaking Capacity @ Rated Voltage	200kA
Size / Dimension 1.110" Dia x 7.880" L (28.19mm x 200.15mm)	Mounting Type	Holder
	Package / Case	Cylindrical, Blade Terminals
Report errors?	Size / Dimension	1.110" Dia x 7.880" L (28.19mm x 200.15mm)
		Report errors?

ECSR80 Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

ECSR80 Payment Methods





















ECSR80 Shipping Methods













If you have any question about ECSR80, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com