

ECW-FA2J225JB

t a Quote

ECW-FA2J225JB Information

Heisener.com	Part Number	ECW-FA2J225JB	
	Manufacturer	Panasonic Electronic Components	
	Category	Capacitors Film Capacitors	
	Description	CAP FILM 2.2UF 5% 630VDC RADIAL	- Sét
	Package	Radial	- 248
		For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Reque

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECW-FA2J225JB Specifications

ManufacturerPanasonic Electronic ComponentsCategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesECW-F(A)Capacitance2.2µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.642" W (26.00mm x 16.30mm)Height - Seated (Max)1.039" (26.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesECW-F(A)Capacitance2.2µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedDoperating Temperature-Operating Temperature-Package / CaseRadialSize / Dimension1.024" L x 0.642" W (26.00mm x 16.30mm)Height - Seated (Max)1.039" (26.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer Part Number	ECW-FA2J225JB
Filn CapacitorsPackageRadialSeriesECW-F(A)Capacitance2.2µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.642" W (26.00mm x 16.30mm)Height - Seated (Max)0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECW-F(A)Capacitance2.2µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.642" W (26.00mm x 16.30mm)Height - Seated (Max)1.039" (26.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Category	Capacitors
SeriesECW-F(A)Capacitance2.2µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.642" W (26.00mm x 16.30mm)Height - Seated (Max)1.039" (26.40mm)TerminationPC PinsApplicationsMigh Frequency, SwitchingFeatures-		Film Capacitors
Capacitance2.2µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension1.024" L x 0.642" W (26.00mm x 16.30mm)Height - Seated (Max)1.039" (26.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.642" W (26.00mm x 16.30mm)Height - Seated (Max)1.039" (26.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Series	ECW-F(A)
Voltage Rating - AC-Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.642" W (26.00mm x 16.30mm)Height - Seated (Max)1.039" (26.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Capacitance	2.2µF
Voltage Rating - DC630VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.642" W (26.00mm x 16.30mm)Height - Seated (Max)1.039" (26.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Tolerance	±5%
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.642" W (26.00mm x 16.30mm)Height - Seated (Max)1.039" (26.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.642" W (26.00mm x 16.30mm)Height - Seated (Max)1.039" (26.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - DC	630V
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" L x 0.642" W (26.00mm x 16.30mm)Height - Seated (Max)1.039" (26.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HoleMounting TypeRadialPackage / CaseRadialSize / Dimension1.024" L x 0.642" W (26.00mm x 16.30mm)Height - Seated (Max)1.039" (26.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.024" L x 0.642" W (26.00mm x 16.30mm)Height - Seated (Max)1.039" (26.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Operating Temperature	$-40^{\circ}C \sim 105^{\circ}C$
Size / Dimension1.024" L x 0.642" W (26.00mm x 16.30mm)Height - Seated (Max)1.039" (26.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Mounting Type	Through Hole
Height - Seated (Max)1.039" (26.40mm)TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Size / Dimension	1.024" L x 0.642" W (26.00mm x 16.30mm)
Lead Spacing0.886" (22.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Height - Seated (Max)	1.039" (26.40mm)
Applications High Frequency, Switching Features -	Termination	PC Pins
Features -	Lead Spacing	0.886" (22.50mm)
	Applications	High Frequency, Switching
Report errors?	Features	-
		Report errors?

ECW-FA2J225JB Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECW-FA2J225JB Payment Methods



ECW-FA2J225JB Shipping Methods



If you have any question about ECW-FA2J225JB, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com