

# ECW-H12102RHV

### **ECW-H12102RHV Information**

Contact service stants there	 ECW-H12102RHV Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 1000PF 3% 1.25KVDC RAD Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **ECW-H12102RHV Specifications**

Manufacturer Part Number   ECW-H12102RHV     Manufacturer   Panasonic Electronic Components     Category   Capacitors     Film Capacitors   Film Capacitors     Package   Radial     Series   ECW-H(V)     Capacitance   1000pF     Tolerance   ±3%     Voltage Rating - AC   -     Voltage Rating - DC   1250V (1.25kV)     Dielectric Material   Polypropylene (PP), Metallized     SSR (Equivalent Series Resistance)   -     Operating Temperature   40°C ~ 105°C     Mounting Type   Through Hole     Package / Case   Radial     Size / Dimension   0.709° L x 0.256° W (18.00mm x 6.50mm)     Height - Seated (Max)   0.728° (18.50mm)     Termination   PC Pins     Lead Spacing   0.295° (7.50mm)     Applications   High Frequency, Switching		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance1000pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric Material010propulenc(PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting Type710rough HolePackage / CaseRadialSize / Dimension0.709" L x 0.256" W (18.00mm x 6.50mm)Height - Seated (Max)0.295" (7.50mm)Lead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer Part Number	ECW-H12102RHV
Fin CapacitorsPackageRadialSeriesECW-H(V)Capacitance1000pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.256" W (18.00mm x 6.50mm)Height - Seated (Max)0.728" (18.50mm)TerminationG295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECW-H(V)Capacitance1000pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 105°CMounting TypeThrough HoleSize / Dimension0.709° L x 0.256° W (18.00mm x 6.50mm)Height - Seated (Max)0.728° (18.50mm)Lead Spacing0.295° (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Category	Capacitors
SeriesECW-H(V)Capacitance1000pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolyproplene (PP), MetallizedDielectric Material-Operating Temperature-Mounting Type-Package / CaseRadialSize / Dimension0.709" L x 0.256" W (18.00mm x 6.50mm)Height - Seated (Max)0.728" (18.50mm)FerninationPipsApplicationsMigh Frequency, SwitchingFeatures.<		Film Capacitors
Capacitance1000pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolyproylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 105°CMounting TypeRadialSize / Dimension0.709" L x 0.256" W (18.00mm x 6.50mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package	Radial
Totance±3%Yoltage Rating - AC-Yoltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.256" W (18.00mm x 6.50mm)Height - Seated (Max)0.728" (18.50mm)TerminationQ295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Series	ECW-H(V)
Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.256" W (18.00mm x 6.50mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Capacitance	1000pF
Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.256" W (18.00mm x 6.50mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Tolerance	±3%
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.256" W (18.00mm x 6.50mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.256" W (18.00mm x 6.50mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - DC	1250V (1.25kV)
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.256" W (18.00mm x 6.50mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.256" W (18.00mm x 6.50mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.709" L x 0.256" W (18.00mm x 6.50mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Operating Temperature	-40°C ~ 105°C
Size / Dimension0.709" L x 0.256" W (18.00mm x 6.50mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Size / Dimension	0.709" L x 0.256" W (18.00mm x 6.50mm)
Lead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Height - Seated (Max)	0.728" (18.50mm)
Applications High Frequency, Switching   Features -	Termination	PC Pins
Features -	Lead Spacing	0.295" (7.50mm)
	Applications	High Frequency, Switching
	Features	-
Report errors'		Report errors?

#### **ECW-H12102RHV Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## **ECW-H12102RHV** Payment Methods



## ECW-H12102RHV Shipping Methods



If you have any question about ECW-H12102RHV, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com