

ECW-H12122RHV

ECW-H12122RHV Information

G	Containerer, Com	 ECW-H12122RHV Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 1200PF 3% 1.25KVDC RAD Radial For the pricing/inventory/lead time, please contact	
	For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECW-H12122RHV Specifications

ManufacturerPanasonic Electronic ComponentsCategoryCapacitorsFalm CapacitorsFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance1200pFTolerance±3%Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropulen (PP), MetallizedDoparating Temperature-Operating Temperature-Voltage / CaseRadialSize / DimensionN009" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)O29" (7.50mm)ApplicationsManufangApplicationsSize / DimensionHeight - Seated (Max)Size / DimensionHeight - Seatering (Size / Dimension)Size / DimensionHe		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance1200pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedSeries Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer Part Number	ECW-H12122RHV
Film CapacitorsPackageRadialSeriesECW-H(V)Capacitance1200pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.728" (18.50mm)Lead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECW-H(V)Capacitance1200pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolyproylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.728" (18.50mm)Lead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Category	Capacitors
ArrowECW-H(V)Capacitance1200pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.728" (18.50mm) x 7.00mm)Height - Seated (Max)0.728" (18.50mm)Lead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-		Film Capacitors
Capacitance1200pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package	Radial
Tolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Series	ECW-H(V)
Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Capacitance	1200pF
Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Tolerance	±3%
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - DC	1250V (1.25kV)
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Operating Temperature	$-40^{\circ}C \sim 105^{\circ}C$
Size / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.728" (18.50mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Size / Dimension	0.709" L x 0.276" W (18.00mm x 7.00mm)
Lead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Height - Seated (Max)	0.728" (18.50mm)
Applications High Frequency, Switching Features -	Termination	PC Pins
Features -	Lead Spacing	0.295" (7.50mm)
	Applications	High Frequency, Switching
Report errors?	Features	-
		Report errors?

ECW-H12122RHV Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECW-H12122RHV Payment Methods



ECW-H12122RHV Shipping Methods



If you have any question about ECW-H12122RHV, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com