

ECW-H12333JVB

ECW-H12333JVB Information

Heisener.com	Part Number Manufacturer Category Description Package	ECW-H12333JVB Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 0.033UF 5% 1.25KVDC RAD Radial For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECW-H12333JVB Specifications

ManufacturerPanasonic Electronic ComponentsCategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.033µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 105°CMounting TypeThrough HoleSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.925" (23.50mm)Lead Spacing0.591" (15.00mm)		
CategoryCapacitorsPackageFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.033µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.925" (23.50mm)Lead Spacing0.591" (15.00mm)	Manufacturer Part Number	ECW-H12333JVB
Fin CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.033µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.925" (23.50mm)Lead Spacing0.591" (15.00mm)	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECW-H(V)Capacitance0.033µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.925" (23.50mm)Lead Spacing0.591" (15.00mm)	Category	Capacitors
Series ECW-H(V) Capacitance 0.033µF Tolerance ±5% Voltage Rating - AC - Voltage Rating - DC 1250V (1.25kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 0.906" L x 0.394" W (23.00mm x 10.00mm) Height - Seated (Max) 0.925" (23.50mm) Lead Spacing 0.591" (15.00mm)		Film Capacitors
Capacitance0.033µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.925" (23.50mm)TerminationCP PinsLead Spacing0.591" (15.00mm)	Package	Radial
Tolerance±5%Yoltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.925" (23.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)	Series	ECW-H(V)
Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.925" (23.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)	Capacitance	0.033µF
Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.925" (23.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.925" (23.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.925" (23.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)	Voltage Rating - DC	1250V (1.25kV)
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.925" (23.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.925" (23.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.925" (23.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)	Operating Temperature	-40°C ~ 105°C
Size / Dimension 0.906" L x 0.394" W (23.00mm x 10.00mm) Height - Seated (Max) 0.925" (23.50mm) Termination PC Pins Lead Spacing 0.591" (15.00mm)	Mounting Type	Through Hole
Height - Seated (Max)0.925" (23.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)	Package / Case	Radial
TerminationPC PinsLead Spacing0.591" (15.00mm)	Size / Dimension	0.906" L x 0.394" W (23.00mm x 10.00mm)
Lead Spacing 0.591" (15.00mm)	Height - Seated (Max)	0.925" (23.50mm)
	Termination	PC Pins
Applications High Frequency Switching	Lead Spacing	0.591" (15.00mm)
representations fight requercy, switching	Applications	High Frequency, Switching
Features -	Features	-
Report errors?		Report errors?

ECW-H12333JVB Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECW-H12333JVB Payment Methods





If you have any question about ECW-H12333JVB, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com