

ECW-H12753HVB

ECW-H12753HVB Information

Heisener.com Gistal arvor statution	 ECW-H12753HVB Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 0.075UF 3% 1.25KVDC RAD Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECW-H12753HVB Specifications

ManufacturerPanasonic Electronic ComponentsCapacitorsFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.075μFTolerance±3%Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolyprophene (PP), MetallizedDoperating Temperature-Operating TypeHrough HolePackage / CaseRadialSize / Dimension1.002" L x 0.531" W (28.00mm x 13.50mm)Height - Seated (Max)1.063" (27.00mm)TerminationPC PinsApplicationsMigh Frequency, Switching		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.075µFTolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.02" L x 0.531" W (28.00mm x 13.50mm)Height - Seated (Max)1.063" (27.00mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer Part Number	ECW-H12753HVB
Film CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.075µFTolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.063" (27.00mm)Height - Seated (Max)0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECW-H(V)Capacitance0.075μFTolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.531" W (28.00mm x 13.50mm)Height - Seated (Max)1.063" (27.00mm)Termination689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Category	Capacitors
Series ECW-H(V) Capacitance 0.075µF Tolerance ±3% Voltage Rating - AC - Voltage Rating - DC 1250V (1.25kV) Dielectric Material Polypropylene (PP), Metallized ESR (Equivalent Series Resistance) - Operating Temperature -40°C ~ 105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.063" (27.00mm) Height - Seated (Max) 0.689" (17.50mm) Lead Spacing 0.689" (17.50mm) Applications High Frequency, Switching Features -		Film Capacitors
Capacitance0.075µFTolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.531" W (28.00mm x 13.50mm)Height - Seated (Max)1.063" (27.00mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package	Radial
Tolerance±3%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.002" L x 0.531" W (28.00mm x 13.50mm)Height - Seated (Max)1.063" (27.00mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Series	ECW-H(V)
Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.531" W (28.00mm x 13.50mm)Height - Seated (Max)Def PinsTerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Capacitance	0.075µF
Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.531" W (28.00mm x 13.50mm)Height - Seated (Max)1.063" (27.00mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Tolerance	±3%
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.531" W (28.00mm x 13.50mm)Height - Seated (Max)1.063" (27.00mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.531" W (28.00mm x 13.50mm)Height - Seated (Max)1.063" (27.00mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - DC	1250V (1.25kV)
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.531" W (28.00mm x 13.50mm)Height - Seated (Max)1.063" (27.00mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.531" W (28.00mm x 13.50mm)Height - Seated (Max)1.063" (27.00mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.102" L x 0.531" W (28.00mm x 13.50mm)Height - Seated (Max)1.063" (27.00mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Operating Temperature	$-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Size / Dimension1.102" L x 0.531" W (28.00mm x 13.50mm)Height - Seated (Max)1.063" (27.00mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Mounting Type	Through Hole
Height - Seated (Max)1.063" (27.00mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Size / Dimension	1.102" L x 0.531" W (28.00mm x 13.50mm)
Lead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Height - Seated (Max)	1.063" (27.00mm)
ApplicationsHigh Frequency, SwitchingFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.689" (17.50mm)
	Applications	High Frequency, Switching
Report errors?	Features	-
		Report errors?

ECW-H12753HVB Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECW-H12753HVB Payment Methods



ECW-H12753HVB Shipping Methods



If you have any question about ECW-H12753HVB, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com