

ECW-H12913JV

ECW-H12913JV Information

Heisener.com Gidal tervice cant terr	 ECW-H12913JV Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 0.091UF 5% 1.25KVDC RAD Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECW-H12913JV Specifications

Manufacturer Part NumberECW-H12913JVManufacturerPanasonic Electronic ComponentsCategoryCapacitorsPackageFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.991µFYoltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedOperating Temperature40°C ~ 105°CMounting TypeThrough HoleSize / Dimension1.102° L x 0.571° W (28.00mm x 14.50mm)Height - Seated (Max)0.965° (24.50mm)Lead Spacing0.984" (25.00mm)AnnlicationsHibe Feruenercy Switching		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.091µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HoleSize / Dimension1.102" L x 0.571"W (28.00mm x 14.50mm)Height - Seated (Max)0.965" (24.50mm)Lead Spacing0.984" (25.00mm)	Manufacturer Part Number	ECW-H12913JV
Fin CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.091μFTolerance±5%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.571" W (28.00mm x 14.50mm)Height - Seated (Max)0.965" (24.50mm)Lead Spacing0.984" (25.00mm)	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECW-H(V)Capacitance0.091µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropelne (PP), MetallizedDisperting Temperature-Operating TypeStrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.571" W (28.00mm x 14.50mm)Height - Seated (Max)0.965" (24.50mm)Lead Spacing0.984" (25.00mm)	Category	Capacitors
Series ECW-H(V) Capacitance 0.091µF Tolerance ±5% Voltage Rating - AC - Voltage Rating - DC 1250V (1.25kV) Dielectric Material Polypropylene (PP), Metallized Dielectric Material - Operating Temperature -40°C ~105°C Mounting Type Through Hole Package / Case Radial Size / Dimension 1.102" L x 0.571" W (28.00mm x 14.50mm) Height - Seated (Max) 0.965" (24.50mm) Lead Spacing 0.984" (25.00mm)		Film Capacitors
Capacitance0.091µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolyproylene (PP), MetallizedDielectric Material-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.965" (24.50mm x 14.50mm)Height - Seated (Max)0.965" (24.50mm)Lead Spacing0.984" (25.00mm)	Package	Radial
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolyropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.02" L x 0.571" W (28.00mm x 14.50mm)Height - Seated (Max)0.965" (24.50mm)TerminationPC PinsLead Spacing0.984" (25.00mm)	Series	ECW-H(V)
Voltage Rating - AC-Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.571" W (28.00mm x 14.50mm)Height - Seated (Max)Operating CaseFerminationPC PinsLead Spacing0.984" (25.00mm)	Capacitance	0.091µF
Voltage Rating - DC1250V (1.25kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.571" W (28.00mm x 14.50mm)Height - Seated (Max)0.965" (24.50mm)TerminationPC PinsLead Spacing0.984" (25.00mm)	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.571" W (28.00mm x 14.50mm)Height - Seated (Max)0.965" (24.50mm)TerminationPC PinsLead Spacing0.984" (25.00mm)	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.571" W (28.00mm x 14.50mm)Height - Seated (Max)0.965" (24.50mm)TerminationPC PinsLead Spacing0.984" (25.00mm)	Voltage Rating - DC	1250V (1.25kV)
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.571" W (28.00mm x 14.50mm)Height - Seated (Max)0.965" (24.50mm)TerminationPC PinsLead Spacing0.984" (25.00mm)	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension1.102" L x 0.571" W (28.00mm x 14.50mm)Height - Seated (Max)0.965" (24.50mm)TerminationPC PinsLead Spacing0.984" (25.00mm)	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension1.102" L x 0.571" W (28.00mm x 14.50mm)Height - Seated (Max)0.965" (24.50mm)TerminationPC PinsLead Spacing0.984" (25.00mm)	Operating Temperature	-40°C ~ 105°C
Size / Dimension 1.102" L x 0.571" W (28.00mm x 14.50mm) Height - Seated (Max) 0.965" (24.50mm) Termination PC Pins Lead Spacing 0.984" (25.00mm)	Mounting Type	Through Hole
Height - Seated (Max)0.965" (24.50mm)TerminationPC PinsLead Spacing0.984" (25.00mm)	Package / Case	Radial
TerminationPC PinsLead Spacing0.984" (25.00mm)	Size / Dimension	1.102" L x 0.571" W (28.00mm x 14.50mm)
Lead Spacing 0.984" (25.00mm)	Height - Seated (Max)	0.965" (24.50mm)
	Termination	PC Pins
Applications High Frequency Switching	Lead Spacing	0.984" (25.00mm)
ripheutons right requeley, switching	Applications	High Frequency, Switching
Features -	Features	-
Report errors		Report errors?

ECW-H12913JV Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECW-H12913JV Payment Methods



ECW-H12913JV Shipping Methods



If you have any question about ECW-H12913JV, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com