

ECW-H20113RJV

ECW-H20113RJV Information

Heisener.com	 ECW-H20113RJV Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 0.011UF 5% 2KVDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECW-H20113RJV Specifications

Manufacturer Part NumberECW-H20113RJVManufacturerPanasonic Electronic ComponentsCategoryCapacitorsPackageFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance011µFTolerance±5%Voltage Rating - AC0000 (2kV)Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-Munufing TypeRadialSize / Dimension900% 1x 0.433" W (23.00mm x 11.00mm)Height - Seated (Max)094" (25.00mm)TerminationPC PinsLad Spacing6.295" (7.50mm)ApplicationsJigh Frequency, SwitchingFeatures.Seatures.		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.011µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HoleSize / Dinension0.906" L x 0.433" W (23.00mm x 11.00mm)Height - Seated (Max)0.984" (25.00mm)TerminationPC PinsLead Spacing0.255" (7.50mm)ApplicationsHigh Frequency, Switching	Manufacturer Part Number	ECW-H20113RJV
Hin CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.011µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HoleSize / Dimension0.906" L x 0.433" W (23.00mm x 11.00mm)Height - Seated (Max)0.984" (25.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, Switching	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECW-H(V)Capacitance0.011µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-40°C ~ 105°CMounting TypeRadialSize / Dimension0.906° L x 0.433° W (23.00mm x 11.00mm)Height - Seated (Max)0.984° (25.00mm)TerminationDC PinsApplications0.925° (7.50mm)ApplicationsHigh Frequency, Switching	Category	Capacitors
SeriesECW-H(V)Capacitance0.011µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 105°CMounting TypeRadialSize / Dimension0.906" L x 0.433" W (23.00mm x 11.00mm)Height - Seated (Max)0.984" (25.00mm)TerminationCP insApplications0.295" (7.50mm)ApplicationsHigh Frequency, Switching		Film Capacitors
Capacitance0.011µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC200V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.906" L x 0.433" W (23.00mm x 11.00mm)Height - Seated (Max)0.984" (25.00mm)Lead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, Switching	Package	Radial
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HoleSize / Dimension0.906" L x 0.433" W (23.00mm x 11.00mm)Height - Seated (Max)0.984" (25.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, Switching	Series	ECW-H(V)
NoticeInterferenceVoltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.433" W (23.00mm x 11.00mm)Height - Seated (Max)0.984" (25.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, Switching	Capacitance	0.011µF
Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.433" W (23.00mm x 11.00mm)Height - Seated (Max)0.984" (25.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, Switching	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.433" W (23.00mm x 11.00mm)Height - Seated (Max)0.984" (25.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, Switching	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.433" W (23.00mm x 11.00mm)Height - Seated (Max)0.984" (25.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, Switching	Voltage Rating - DC	2000V (2kV)
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.433" W (23.00mm x 11.00mm)Height - Seated (Max)0.984" (25.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, Switching	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.433" W (23.00mm x 11.00mm)Height - Seated (Max)0.984" (25.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, Switching	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.906" L x 0.433" W (23.00mm x 11.00mm)Height - Seated (Max)0.984" (25.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, Switching	Operating Temperature	-40°C ~ 105°C
Size / Dimension 0.906" L x 0.433" W (23.00mm x 11.00mm) Height - Seated (Max) 0.984" (25.00mm) Termination PC Pins Lead Spacing 0.295" (7.50mm) Applications High Frequency, Switching	Mounting Type	Through Hole
Height - Seated (Max)0.984" (25.00mm)TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, Switching	Package / Case	Radial
TerminationPC PinsLead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, Switching	Size / Dimension	0.906" L x 0.433" W (23.00mm x 11.00mm)
Lead Spacing0.295" (7.50mm)ApplicationsHigh Frequency, Switching	Height - Seated (Max)	0.984" (25.00mm)
Applications High Frequency, Switching	Termination	PC Pins
	Lead Spacing	0.295" (7.50mm)
Features -	Applications	High Frequency, Switching
	Features	-
Report errors?		Report errors?

ECW-H20113RJV Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECW-H20113RJV Payment Methods



ECW-H20113RJV Shipping Methods



If you have any question about ECW-H20113RJV, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com