

ECW-H20122HV

a Quote

ECW-H20122HV Information

Heisener.com	Part Number	ECW-H20122HV	
	Manufacturer	Panasonic Electronic Components	
	Category	Capacitors Film Capacitors	232
	Description	CAP FILM 1200PF 3% 2KVDC RADIAL	- SERK
	Package	Radial	
		For the pricing/inventory/lead time, please contact	「国や
For Reference Only			
		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECW-H20122HV Specifications

Manufacturer Part NumberECW-H20122HVManufacturerPanasonic Electronic ComponentsCategoryCapacitorsPackageRadialPackageRadialSeriesECW-H(V)Capacitance1200pFTolerance±3%Voltage Rating - AC000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedOperating Temperature-Operating TemperatureAdi02 ~ 105°CNounting TypeThrough HoleStaze / CaseRadialSize / Dimension0.59°L x 0.276°W (18.00mm x 7.00mm)Height - Seated (Max)0.591°L f1.500mmIterminationGPI Prevency, SwitchingApplicationsMing Frequency, SwitchingFeatures-		
CategoryCapacitorsPackageRadialPackageRadialSeriesECW-H(V)Capacitance1200pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HoleSize / Dimension0.501" (15.00mm) x .00mm) x .00mm)Height - Seated (Max)0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Manufacturer Part Number	ECW-H20122HV
Film CapacitorsPackageRadialSeriesECW-H(V)Capacitance1200pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HoleSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.591" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsMigh Frequency, Switching	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECW-H(V)Capacitance1200pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedDielectric Material-Operating Temperature-Mounting TypeHough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.591" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Category	Capacitors
SeriesECW-H(V)Capacitance1200pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedDielectric Material-Operating Temperature-40°C ~ 105°CMounting TypeHoluga HoluePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.591" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching		Film Capacitors
Capacitance1200pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.501" (15.00mm x 7.00mm)Height - Seated (Max)0.591" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Package	Radial
Tolerance±3%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.591" (15.00mm) x7.00mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Series	ECW-H(V)
Voltage Rating - AC-Voltage Rating - DC200V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.509" (15.00mm) x 7.00mm)Height - Seated (Max)PC PinsLead Spacing0.591" (15.00mm)Heigh Seated (Max)High Frequency, Switching	Capacitance	1200pF
Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.591" (15.00mm)Termination0.591" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Tolerance	$\pm 3\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Voltage Rating - DC	2000V (2kV)
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.709" L x 0.276" W (18.00mm x 7.00mm)Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Operating Temperature	-40°C ~ 105°C
Size / Dimension 0.709" L x 0.276" W (18.00mm x 7.00mm) Height - Seated (Max) 0.591" (15.00mm) Termination PC Pins Lead Spacing 0.591" (15.00mm) Applications High Frequency, Switching	Mounting Type	Through Hole
Height - Seated (Max)0.591" (15.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Package / Case	Radial
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Size / Dimension	0.709" L x 0.276" W (18.00mm x 7.00mm)
Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching	Height - Seated (Max)	0.591" (15.00mm)
Applications High Frequency, Switching	Termination	PC Pins
	Lead Spacing	0.591" (15.00mm)
Features -	Applications	High Frequency, Switching
	Features	-
Report error		Report errors?

ECW-H20122HV Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECW-H20122HV Payment Methods



ECW-H20122HV Shipping Methods



If you have any question about ECW-H20122HV, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com