

# ECW-H20133JVB

### **ECW-H20133JVB Information**

Heisener.com	Part Number Manufacturer Category Description Package	ECW-H20133JVB Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 0.013UF 5% 2KVDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



## **ECW-H20133JVB** Specifications

ManufacturerPanasonic Electronic ComponentsCategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.013μFTolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.024" (26.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, Switching		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.013µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.024" (26.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer Part Number	ECW-H20133JVB
Film CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.013 µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.024" (26.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECW-H(V)Capacitance0.013µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.024" (26.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Category	Capacitors
Beries ECW-H(V)   Capacitance 0.013µF   Tolerance ±5%   Voltage Rating - AC -   Voltage Rating - DC 2000V (2kV)   Dielectric Material Polypropylene (PP), Metallized   ESR (Equivalent Series Resistance) -   Operating Temperature -40°C ~ 105°C   Mounting Type Through Hole   Package / Case Radial   Size / Dimension 1.024" (26.00mm) x 12.00mm x 12.00mm)   Height - Seated (Max) 1.024" (26.00mm)   Lead Spacing 0.591" (15.00mm)   Applications High Frequency, Switching   Features -		Film Capacitors
Capacitance0.013µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension1.024" (26.00mm) x 12.00mm x 12.00mm)Height - Seated (Max)1.024" (26.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.024" (26.00mm x 12.00mm x 12.00mm)Height - Seated (Max)0.591" (15.00mm)Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Series	ECW-H(V)
Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.024" (26.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Capacitance	0.013µF
Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.024" (26.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.024" (26.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.024" (26.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - DC	2000V (2kV)
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.024" (26.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HoleMounting TypeRadialPackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.024" (26.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.024" (26.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Size / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.024" (26.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Mounting Type	Through Hole
Height - Seated (Max)1.024" (26.00mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Size / Dimension	0.906" L x 0.472" W (23.00mm x 12.00mm)
Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Height - Seated (Max)	1.024" (26.00mm)
ApplicationsHigh Frequency, SwitchingFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.591" (15.00mm)
	Applications	High Frequency, Switching
Report errors?	Features	-
		Report errors?

#### **ECW-H20133JVB Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **ECW-H20133JVB Payment Methods**



## **ECW-H20133JVB Shipping Methods**



If you have any question about ECW-H20133JVB, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com