

# ECW-H20153JVB

a Quote

#### **ECW-H20153JVB Information**

Heisener.com	Part Number	ECW-H20153JVB	
	Manufacturer	Panasonic Electronic Components	_ ∎28
	Category	Capacitors Film Capacitors	
	Description	CAP FILM 0.015UF 5% 2KVDC RADIAL	- 第54
	Package	Radial	
		For the pricing/inventory/lead time, please contact	ାଆଙ
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **ECW-H20153JVB** Specifications

ManufacturerPanasonic Electronic ComponentsCategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.015 µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedSeries Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.043" (26.50mm)TerminationPC PinsLead Spacing.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.015µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedSeries Resistance)-Operating Temperature40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.043" (26.50mm)TerminationPC PinsLead Spacing.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer Part Number	ECW-H20153JVB
Film CapacitorsPackageRadialSeriesECW-H(V)Capacitance0.015µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906° L x 0.472° W (23.00mm x 12.00mm)Height - Seated (Max)1.043° (26.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECW-H(V)Capacitance0.015µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.043" (26.50mm)TerminationSp1" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Category	Capacitors
Series   ECW-H(V)     Capacitance   0.015µF     Tolerance   ±5%     Voltage Rating - AC   -     Voltage Rating - DC   2000V (2kV)     Dielectric Material   Polypropylene (PP), Metallized     ESR (Equivalent Series Resistance)   -     Operating Temperature   -40°C ~ 105°C     Mounting Type   Through Hole     Package / Case   Radial     Size / Dimension   0.906" L x 0.472" W (23.00mm x 12.00mm)     Height - Seated (Max)   1.043" (26.50mm)     Termination   PC Pins     Lead Spacing   0.591" (15.00mm)     Applications   High Frequency, Switching     Features   -		Film Capacitors
Capacitance0.015µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension1.043" (26.50mm) x 12.00mm x 12.00mm)Height - Seated (Max)1.043" (26.50mm)Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package	Radial
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension1.043" (26.50mm x 12.00mm x 12.00mm)Height - Seated (Max)1.043" (26.50mm)Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Series	ECW-H(V)
Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.043" (26.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Capacitance	0.015µF
Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.043" (26.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Tolerance	$\pm 5\%$
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.043" (26.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.043" (26.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - DC	2000V (2kV)
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.043" (26.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.043" (26.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.906" L x 0.472" W (23.00mm x 12.00mm)Height - Seated (Max)1.043" (26.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Size / Dimension 0.906" L x 0.472" W (23.00mm x 12.00mm)   Height - Seated (Max) 1.043" (26.50mm)   Termination PC Pins   Lead Spacing 0.591" (15.00mm)   Applications High Frequency, Switching   Features -	Mounting Type	Through Hole
Height - Seated (Max)1.043" (26.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Size / Dimension	0.906" L x 0.472" W (23.00mm x 12.00mm)
Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Height - Seated (Max)	1.043" (26.50mm)
ApplicationsHigh Frequency, SwitchingFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.591" (15.00mm)
	Applications	High Frequency, Switching
Report errors?	Features	-
		Report errors?

#### **ECW-H20153JVB Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

# **ECW-H20153JVB Payment Methods**



#### 

If you have any question about ECW-H20153JVB, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com