

# ECW-H20822HV

## **ECW-H20822HV Information**

Heisener.com	 ECW-H20822HV Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 8200PF 3% 2KVDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# **ECW-H20822HV** Specifications

Manufacturer Panasonic Electronic Components   Capacitors Film Capacitors   Package Radial   Series ECW-H(V)   Capacitance 8200pF   Tolerance ±3%   Voltage Rating - DC 2000V (2kV)   Dielectric Material Polypopylene (PP), Metallized   Operating Temperature -   Agdial 40°C ~ 105°C   Notunting Type Hough Hole   Size / Dimension 0.906" L x 0.394" W (23.00mm x 10.00mm)   Height - Seated (Max) 0.768" (19.50mm)   Termination PC Pins   Lead Spacing 0.787" (20.00mm)   Applications 1.616 Frequency, Switching   Features -		
CapacitorsFilm CapacitorsPackageRadialSeriesECW-H(V)Capacitance8200pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer Part Number	ECW-H20822HV
Fin CapacitorsPackageRadialSeriesECW-H(V)Capacitance8200pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.768" (19.50mm)TerminationPC PinsLead Spacing0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer	Panasonic Electronic Components
PackageRadiaSeriesECW-H(V)Capacitance8200pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.768" (19.50mm)TerminationPC PinsLead Spacing0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Category	Capacitors
Series ECW-H(V)   Capacitance 8200pF   Tolerance ±3%   Yoltage Rating - AC -   Voltage Rating - DC 2000V (2kV)   Dielectric Material Polypropylene (PP), Metallized   ESR (Equivalent Series Resistance) -   Operating Temperature -40°C ~ 105°C   Mounting Type Through Hole   Package / Case Radial   Size / Dimension 0.906" L x 0.394" W (23.00mm x 10.00mm)   Height - Seated (Max) 0.768" (19.50mm)   Lead Spacing 0.787" (20.00mm)   Applications High Frequency, Switching   Features -		Film Capacitors
Capacitance8200pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.768" (19.50mm)TerminationPC PinsLead Spacing0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package	Radial
Tolerance±3%Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.768" (19.50mm)TerminationPC PinsLead Spacing0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Series	ECW-H(V)
Voltage Rating - AC-Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.768" (19.50mm)TerminationPC PinsLead Spacing0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Capacitance	8200pF
Voltage Rating - DC2000V (2kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.768" (19.50mm)TerminationPC PinsLead Spacing0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Tolerance	±3%
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.768" (19.50mm)TerminationPC PinsLead Spacing0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-Mounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.768" (19.50mm)TerminationPC PinsLead Spacing0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - DC	2000V (2kV)
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.768" (19.50mm)TerminationPC PinsLead Spacing0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Notified TypeThrough HoleMounting TypeRadialPackage / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.768" (19.50mm)TerminationPC PinsLead Spacing0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.768" (19.50mm)TerminationPC PinsLead Spacing0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Operating Temperature	$-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$
Size / Dimension0.906" L x 0.394" W (23.00mm x 10.00mm)Height - Seated (Max)0.768" (19.50mm)TerminationPC PinsLead Spacing0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.768" (19.50mm)TerminationPC PinsLead Spacing0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Size / Dimension	0.906" L x 0.394" W (23.00mm x 10.00mm)
Lead Spacing0.787" (20.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Height - Seated (Max)	0.768" (19.50mm)
ApplicationsHigh Frequency, SwitchingFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.787" (20.00mm)
	Applications	High Frequency, Switching
Report errors?	Features	-
		Report errors?

#### **ECW-H20822HV Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

### **ECW-H20822HV Payment Methods**



# **ECW-H20822HV** Shipping Methods



If you have any question about ECW-H20822HV, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com