

ECW-H8472HL

ECW-H8472HL Information

Heisener.com	 ECW-H8472HL Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 4700PF 3% 800VDC RADIAL Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECW-H8472HL Specifications

ManufacturerPanasonic Electronic ComponentsCategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesECW-H(L)Capacitance4700pFTolerance±3%Voltage Rating - AC>Voltage Rating - DCB00VDielectric Material-Operating Temperature-Operating Temperature-Voltage / CaseRadialSize / Dimension0.700° L x 0.197° W (18.00mm x 5.00mm)Height - Seated (Max)0.521° (13.00mm)TerminationPC PinsLead Spacing-Applications5.91° (15.00mm)Features-Features-Features-Features-Capacitons- </th <th></th> <th></th>		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesECW-H(L)Capacitance4700pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.532" (13.50mm)Height - Seated (Max)0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer Part Number	ECW-H8472HL
Filn CapacitorsPackageRadialSeriesECW-H(L)Capacitance4700pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.197" W (18.00mm x 5.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECW-H(L)Capacitance4700pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolyproplene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.197" W (18.00mm x 5.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Category	Capacitors
YearECW-H(L)Capacitance4700pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature40°C ~ 110°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.532" (13.50mm) x 5.00mm)Height - Seated (Max)0.531" (15.00mm)Applications0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-		Film Capacitors
Capacitance4700pFTolerance±3%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.532" (13.50mm)Height - Seated (Max)0.532" (13.50mm)Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package	Radial
Tolerance±3%Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.197" W (18.00mm x 5.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Series	ECW-H(L)
Voltage Rating - AC-Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.197" W (18.00mm x 5.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Capacitance	4700pF
Voltage Rating - DC800VDielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.197" W (18.00mm x 5.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Tolerance	±3%
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.197" W (18.00mm x 5.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.197" W (18.00mm x 5.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - DC	800V
Operating Temperature-40°C ~ 110°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.197" W (18.00mm x 5.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.709" L x 0.197" W (18.00mm x 5.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.709" L x 0.197" W (18.00mm x 5.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Operating Temperature	-40°C ~ 110°C
Size / Dimension0.709" L x 0.197" W (18.00mm x 5.00mm)Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.532" (13.50mm)TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Size / Dimension	0.709" L x 0.197" W (18.00mm x 5.00mm)
Lead Spacing0.591" (15.00mm)ApplicationsHigh Frequency, SwitchingFeatures-	Height - Seated (Max)	0.532" (13.50mm)
ApplicationsHigh Frequency, SwitchingFeatures-	Termination	PC Pins
Features -	Lead Spacing	0.591" (15.00mm)
	Applications	High Frequency, Switching
Report errors?	Features	-
		Report errors?

ECW-H8472HL Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECW-H8472HL Payment Methods



ECW-H8472HL Shipping Methods



If you have any question about ECW-H8472HL, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com