

# ECW-HA3C103JQ

### ECW-HA3C103JQ Information

Contact service statistics	ECW-HA3C103JQ Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 10000PF 5% 1.6KVDC RAD Radial For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



### **ECW-HA3C103JQ Specifications**

ManufacturerPanasonic Electronic ComponentsCategoryCapacitorsFilm CapacitorsFilm CapacitorsPackageRadialSeriesECW-H(A)Capacitance10000pFTolerance±5%Voltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedStress Resistance)-Operating Temperature-40°C ~ 105°CNounting TypeThrough HolePackage / CaseRadialSize / Dimension0.681" (17.30mm)Height - Seated (Max)Oc 89" (17.50mm)ApplicationsMis Frequency, Switching		
CategoryCapacitorsFilm CapacitorsPackageRadialSeriesECW-H(A)Capacitance1000pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.799" L x 0.252" W (20.30mm x 6.40mm)Height - Seated (Max)0.681" (17.30mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer Part Number	ECW-HA3C103JQ
Film CapacitorsPackageRadialSeriesECW-H(A)Capacitance10000pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.799" L x 0.252" W (20.30mm x 6.40mm)Height - Seated (Max)0.681" (17.30mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Manufacturer	Panasonic Electronic Components
PackageRadialSeriesECW-H(A)Capacitance10000pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC1600V (1.6kV)Dielectric MaterialPolyproylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.799" L x 0.252" W (20.30mm x 6.40mm)Height - Seated (Max)0.681" (17.30mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Category	Capacitors
SeriesECW-H(A)Capacitance10000pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeRadialPackage / CaseRadialSize / Dimension0.799" L x 0.252" W (20.30mm x 6.40mm)Height - Seated (Max)0.681" (17.30mm)Lead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-		Film Capacitors
Capacitance10000pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.799" L x 0.252" W (20.30mm x 6.40mm)Height - Seated (Max)0.681" (17.30mm)TerminationPC PinsLead Spacing0.689" (17.50mm)Applications-Features-	Package	Radial
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.681" (17.30mm)Height - Seated (Max)0.689" (17.50mm)Lead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Series	ECW-H(A)
Voltage Rating - AC-Voltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.799" L x 0.252" W (20.30mm x 6.40mm)Height - Seated (Max)0.681" (17.30mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Capacitance	10000pF
Voltage Rating - DC1600V (1.6kV)Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.799" L x 0.252" W (20.30mm x 6.40mm)Height - Seated (Max)0.681" (17.30mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Tolerance	±5%
Dielectric MaterialPolypropylene (PP), MetallizedESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.799" L x 0.252" W (20.30mm x 6.40mm)Height - Seated (Max)0.681" (17.30mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - AC	-
ESR (Equivalent Series Resistance)-Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.799" L x 0.252" W (20.30mm x 6.40mm)Height - Seated (Max)0.681" (17.30mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Voltage Rating - DC	1600V (1.6kV)
Operating Temperature-40°C ~ 105°CMounting TypeThrough HolePackage / CaseRadialSize / Dimension0.799" L x 0.252" W (20.30mm x 6.40mm)Height - Seated (Max)0.681" (17.30mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Dielectric Material	Polypropylene (PP), Metallized
Nounting TypeThrough HolePackage / CaseRadialSize / Dimension0.799" L x 0.252" W (20.30mm x 6.40mm)Height - Seated (Max)0.681" (17.30mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	ESR (Equivalent Series Resistance)	-
Package / CaseRadialSize / Dimension0.799" L x 0.252" W (20.30mm x 6.40mm)Height - Seated (Max)0.681" (17.30mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Operating Temperature	$-40^{\circ}\mathrm{C} \sim 105^{\circ}\mathrm{C}$
Size / Dimension0.799" L x 0.252" W (20.30mm x 6.40mm)Height - Seated (Max)0.681" (17.30mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Mounting Type	Through Hole
Height - Seated (Max)0.681" (17.30mm)TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Package / Case	Radial
TerminationPC PinsLead Spacing0.689" (17.50mm)ApplicationsHigh Frequency, SwitchingFeatures-	Size / Dimension	0.799" L x 0.252" W (20.30mm x 6.40mm)
Lead Spacing 0.689" (17.50mm)   Applications High Frequency, Switching   Features -	Height - Seated (Max)	0.681" (17.30mm)
Applications High Frequency, Switching   Features -	Termination	PC Pins
Features -	Lead Spacing	0.689" (17.50mm)
	Applications	High Frequency, Switching
Report errors?	Features	-
		Report errors?

#### **ECW-HA3C103JQ Guarantees**



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

#### **ECW-HA3C103JQ Payment Methods**



### ECW-HA3C103JQ Shipping Methods



If you have any question about ECW-HA3C103JQ, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com