

# ECW-U1H392JB5

#### ECW-U1H392JB5 Information

www.belsencom	 ECW-U1H392JB5 Panasonic Electronic Components Capacitors Film Capacitors CAP FILM 3900PF 5% 50VDC 1206 1206 (3216 Metric) For the pricing/inventory/lead time, please contact	
For Reference Only	us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

## **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



# ECW-U1H392JB5 Specifications

Manufacturer     Panasonic Electronic Components       Capacitors     Film Capacitors       Package     1206 (3216 Metric)       Series     ECW-U(B)       Capacitance     3900pF       Tolerance     ±5%       Voltage Rating - DC     50V       Dielectric Material     Polyester, Polyethylene Naphthalate (PEN), Metallized - Stacked       Doperating Temperature     -       Agade / Case     1206 (3216 Metric)       Size / Dimension     -       Mounting Type     -       Package / Case     1206 (3216 Metric)       Size / Dimension     0.126° L x 0.063° W (3.20mm x 1.60mm)       Height - Seated (Max)     0.039° (1.00mm)       Termination     Solder Pads       Lead Spacing     -       Applications     -       Stoler Pads     -       Stol			
CategoryCapacitorsFilm CapacitorsPackage1206 (3216 Metric)SeriesECW-U(B)Capacitance3900pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063° W (3.20mm x 1.60mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Manufacturer Part Number	ECW-U1H392JB5	
Fin CapacitorsPackage1206 (3216 Metric)SeriesECW-U(B)Capacitance3900pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Manufacturer	Panasonic Electronic Components	
Package1206 (3216 Metric)SeriesECW-U(B)Capacitance3900pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126° L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.039" (1.00mm)Lead Spacing-ApplicationsGeneral PurposeFeatures-Seatures-	Category	Capacitors	
SeriesECW-U(B)Capacitance3900pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-		Film Capacitors	
Capacitance3900pFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package	1206 (3216 Metric)	
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Series	ECW-U(B)	
Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Capacitance	3900pF	
Voltage Rating - DC50VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Tolerance	$\pm 5\%$	
Dielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	-	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	50V	
Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyester, Polyethylene Naphthalate (PEN), Metallized - Stacked	
Notified TypeSurface MountMounting TypeSurface MountPackage / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-	
Package / Case1206 (3216 Metric)Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 105°C	
Size / Dimension0.126" L x 0.063" W (3.20mm x 1.60mm)Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Mounting Type	Surface Mount	
Height - Seated (Max)0.039" (1.00mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package / Case	1206 (3216 Metric)	
Termination Solder Pads   Lead Spacing -   Applications General Purpose   Features -	Size / Dimension	0.126" L x 0.063" W (3.20mm x 1.60mm)	
Lead Spacing-ApplicationsGeneral PurposeFeatures-	Height - Seated (Max)	0.039" (1.00mm)	
ApplicationsGeneral PurposeFeatures-	Termination	Solder Pads	
Features -	Lead Spacing	-	
	Applications	General Purpose	
Report errors?	Features	-	
			Report errors?

#### ECW-U1H392JB5 Guarantees



Quality Guarantees

We provide 90 days warranty. \* If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

# SERVICE BUARANTEE

#### **Service Guarantees**

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

## ECW-U1H392JB5 Payment Methods



#### ECW-U1H392JB5 Shipping Methods



If you have any question about ECW-U1H392JB5, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com