

ECW-U1H683JB9

ECW-U1H683JB9 Information

www.chelsenerom		ECW-U1H683JB9 Panasonic Electronic Components Capacitors	
	Description Package	Film Capacitors CAP FILM 0.068UF 5% 50VDC 1913 1913 (4833 Metric)	
For Deformed Only	I ackage	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com	■約約3
For Reference Only		E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECW-U1H683JB9 Specifications

ManufacturerPanasonic Electronic ComponentsCapacitorsFilm CapacitorsPackage1913 (4833 Metric)SeriesECW-U(B)Capacitance0.068µFFolerance±5% CapacitonsVoltage Rating - AC50VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedDielectric Material-Operating Temperature-5°C ~ 105°CPackage / Case1913 (4833 Metric)Size / Dimension0.087" (2.0mm)Bieght - Seated (Max)0.087" (2.0mm)Capacitagi-Capacitagi <th></th> <th></th> <th></th>			
CategoryCapacitorsFilm CapacitorsPackage1913 (4833 Metric)PackageECW-U(B)Capacitance0.068µFCapacitance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedDielectric Material-Operating Temperature-55°C ~ 105°CPackage / Case1913 (4833 Metric)Size / Dimension0.189° L x 0.130° W (4.80mm x 3.30mm)Height - Seated (Max)0.087" (2.20mm)FerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Manufacturer Part Number	ECW-U1H683JB9	
Fin CapacitorsPackage1913 (4833 Metric)SeriesECW-U(B)Capacitance0.068µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1913 (4833 Metric)Size / Dimension0.189" L x 0.130" W (4.80mm x 3.30mm)Height - Seated (Max)0.087" (2.20mm)Chead Spacing-ApplicationsGeneral PurposeFeatures-Seatures-Statures-Applications-Statures-	Manufacturer	Panasonic Electronic Components	
Package1913 (4833 Metric)SeriesECW-U(B)Capacitance0.068µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedDietertic Material-Operating Temperature-Operating TypeSurface MountPackage / Case1913 (4833 Metric)Size / Dimension0.887" (2.20mm)Height - Seated (Max)0.087" (2.20mm)Lead Spacing-ApplicationsGeneral PurposeFeatures-Seatures-	Category	Capacitors	
SeriesECW-U(B)Capacitance0.068µFFolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CPackage / Case1913 (4833 Metric)Size / Dimension0.087" (2.20mm)Height - Seated (Max)0.087" (2.20mm)FerminationSolder PadsLead Spacing-Features-Features-		Film Capacitors	
Capacitance0.068µFFolerance±5%Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1913 (4833 Metric)Size / Dimension0.087" (2.20mm)Height - Seated (Max)Solder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package	1913 (4833 Metric)	
Folerance±5%Voltage Rating - AC-Voltage Rating - DC50VDelectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1913 (4833 Metric)Size / Dimension0.189" L x 0.130" W (4.80mm x 3.30mm)Height - Seated (Max)0.087" (2.20mm)FerminationSolder PadsLead Spacing-Features-Features-	Series	ECW-U(B)	
Voltage Rating - AC-Voltage Rating - DC50VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1913 (4833 Metric)Size / Dimension0.189" L x 0.130" W (4.80mm x 3.30mm)Height - Seated (Max)0.087" (2.20mm)FerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Capacitance	0.068µF	
Voltage Rating - DC50VDelectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1913 (4833 Metric)Bize / Dimension0.189° L x 0.130° W (4.80mm x 3.30mm)Height - Seated (Max)0.087" (2.20mm)FerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Tolerance	±5%	
Dielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1913 (4833 Metric)Size / Dimension0.189" L x 0.130" W (4.80mm x 3.30mm)Height - Seated (Max)0.087" (2.20mm)FerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - AC	-	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1913 (4833 Metric)Oitse / Dimension0.189" L x 0.130" W (4.80mm x 3.30mm)Height - Seated (Max)0.087" (2.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Voltage Rating - DC	50V	
Derating Temperature-55°C ~ 105°CMounting TypeSurface MountPackage / Case1913 (4833 Metric)Package / Case0.189" L x 0.130" W (4.80mm x 3.30mm)Size / Dimension0.087" (2.20mm)Height - Seated (Max)0.087" (2.20mm)FerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Dielectric Material	Polyester, Polyethylene Naphthalate (PEN), Metallized - Stacked	
Nontrig TypeSurface MountPackage / Case1913 (4833 Metric)Package / Case0.189" L x 0.130" W (4.80mm x 3.30mm)Bize / Dimension0.087" (2.20mm)Height - Seated (Max)0.087" (2.20mm)FerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	ESR (Equivalent Series Resistance)	-	
Package / Case1913 (4833 Metric)Size / Dimension0.189" L x 0.130" W (4.80mm x 3.30mm)Height - Seated (Max)0.087" (2.20mm)FerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Operating Temperature	-55°C ~ 105°C	
Size / Dimension0.189" L x 0.130" W (4.80mm x 3.30mm)Height - Seated (Max)0.087" (2.20mm)TerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Mounting Type	Surface Mount	
Height - Seated (Max)0.087" (2.20mm)FerminationSolder PadsLead Spacing-ApplicationsGeneral PurposeFeatures-	Package / Case	1913 (4833 Metric)	
Termination Solder Pads Lead Spacing - Applications General Purpose Features -	Size / Dimension	0.189" L x 0.130" W (4.80mm x 3.30mm)	
Lead Spacing - Applications General Purpose Features -	Height - Seated (Max)	0.087" (2.20mm)	
Applications General Purpose Features -	Termination	Solder Pads	
Features -	Lead Spacing	-	
	Applications	General Purpose	
Report errors?	Features	-	
			Report errors?

ECW-U1H683JB9 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE ELARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECW-U1H683JB9 Payment Methods



ECW-U1H683JB9 Shipping Methods



If you have any question about ECW-U1H683JB9, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com