

ECW-U2823V16

a Quote

ECW-U2823V16 Information

	Part Number	ECW-U2823V16	
	Manufacturer	Panasonic Electronic Components	ा चा इन्द्र
and the	Category	Capacitors Film Capacitors	
	Description	CAP FILM 0.082UF 5% 250VDC 2420	- 7824
	Package	2420 (6050 Metric)	
		For the pricing/inventory/lead time, please contact us	1 24
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECW-U2823V16 Specifications

Manufacturer Part Number ECW-U2823V16 Manufacturer Panasonic Electronic Components Category Capacitors Film Capacitors Film Capacitors Package 2420 (6050 Metric) Series ECW-U(V16) Capacitance 0.082µF Yoltage Rating - AC - Voltage Rating - DC 250V Dielectric Material Polysetr, Polysthylene Naphthalate (PEN), Metallized - Stacked Strike Capacitance - Operating Temperature -55°C ~ 85°C Mounting Type Surface Mount Package / Case 2420 (6050 Metric) Size / Dimension 0.236° L x 0.197" W (6.00mm x 5.00mm) Height - Seated (Max) 0.38" (3.50mm) Termination Solder Pads Lead Spacing - Applications High Frequency, Switching; High Pulse, DV/DT Features -			
CategoryCapacitorsFilm CapacitorsPackage2420 (6050 Metric)SeriesECW-U(V16)Capacitance0.082µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC250VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedSer (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeSurface MountPackage / Case2420 (6050 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max).138" (3.50mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer Part Number	ECW-U2823V16	
Fin CapacitorsPackage2420 (6050 Metric)SeriesECW-U(V16)Capacitance0.082µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC250VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeSurface MountPackage / Case2420 (6050 Metric)Size / Dimension0.138" (3.50mm)Height - Seated (Max)0.138" (3.50mm)Lead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Manufacturer	Panasonic Electronic Components	
Package2420 (6050 Metric)SeriesECW-U(V16)Capacitance0.082µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC250VDielectric MaterialPolyester, Polyethylene Naphthalte (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeSurface MountPackage / Case2420 (6050 Metric)Size / Dimension0.236° L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)Solder PadsLead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Category	Capacitors	
SeriesECW-U(V16)Capacitance0.082µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC250VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeSurface MountPackage / Case2420 (6050 Metric)Size / Dimension0.138" (3.50mm)Height - Seated (Max)50der PadsLead Spacing-ApplicationsFrequency, Switching; High Pulse, DV/DTFeatures-		Film Capacitors	
Capacitance0.082µFTolerance±5%Voltage Rating - AC-Voltage Rating - DC250VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeSurface MountPackage / Case2420 (6050 Metric)Size / Dimension0.138" (3.50mm)Height - Seated (Max)0.138" (3.50mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Package	2420 (6050 Metric)	
Tolerance±5%Voltage Rating - AC-Voltage Rating - DC250VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeSurface MountPackage / Case2420 (6050 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)Solder PadsLead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Series	ECW-U(V16)	
Voltage Rating - AC-Voltage Rating - DC250VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeSurface MountPackage / Case2420 (6050 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)Solder PadsLead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Capacitance	0.082µF	
Voltage Rating - DC250VDielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeSurface MountPackage / Case2420 (6050 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)0.138" (3.50mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Tolerance	$\pm 5\%$	
Dielectric MaterialPolyester, Polyethylene Naphthalate (PEN), Metallized - StackedESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeSurface MountPackage / Case2420 (6050 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)0.138" (3.50mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - AC	-	
ESR (Equivalent Series Resistance)-Operating Temperature-55°C ~ 85°CMounting TypeSurface MountPackage / Case2420 (6050 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)0.138" (3.50mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Voltage Rating - DC	250V	
Operating Temperature-55°C ~ 85°CMounting TypeSurface MountPackage / Case2420 (6050 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)0.138" (3.50mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Dielectric Material	Polyester, Polyethylene Naphthalate (PEN), Metallized - Stacked	
Mounting TypeSurface MountPackage / Case2420 (6050 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)0.138" (3.50mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	ESR (Equivalent Series Resistance)	-	
Package / Case2420 (6050 Metric)Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)0.138" (3.50mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Operating Temperature	-55°C ~ 85°C	
Size / Dimension0.236" L x 0.197" W (6.00mm x 5.00mm)Height - Seated (Max)0.138" (3.50mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Mounting Type	Surface Mount	
Height - Seated (Max)0.138" (3.50mm)TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Package / Case	2420 (6050 Metric)	
TerminationSolder PadsLead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Size / Dimension	0.236" L x 0.197" W (6.00mm x 5.00mm)	
Lead Spacing-ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Height - Seated (Max)	0.138" (3.50mm)	
ApplicationsHigh Frequency, Switching; High Pulse, DV/DTFeatures-	Termination	Solder Pads	
Features -	Lead Spacing	-	
	Applications	High Frequency, Switching; High Pulse, DV/DT	
Report errors?	Features	-	
			Report errors?

ECW-U2823V16 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE UARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECW-U2823V16 Payment Methods



ECW-U2823V16 Shipping Methods



If you have any question about ECW-U2823V16, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com