

ECX-L33BN-125.000

ECX-L33BN-125.000 Information

Heisener.com	Part Number Manufacturer Category Description Package	ECX-L33BN-125.000 ECS Inc. Crystals, Oscillators, Resonators Oscillators OSC XO 125.0000MHZ LVDS SMD 6-SMD, No Lead For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



ECX-L33BN-125.000 Specifications

AnufacturerECS Inc.AttegoryCrystals, Oscillators, ResonatorsOscillatorsOscillatorsackage6-SMD, No LeadackageECS pressCON? ECX-LypeXO (Standard)requency125MHzunctionEnable/Disablevoltage - Supply3.3Vrequency Stability±50ppmuperating Temperature40°C ~ 85°Current - Supply (Max)20mA		
Crystals, Oscillators, Resonators Oscillators ackage 6-SMD, No Lead eries 6-SMD, No Lead eries ECSpressCON? ECX-L ype XO (Standard) requency 125MHz unction Enable/Disable voltage - Supply 3.3V requency Stability ±50ppm voltage Temperature -40°C ~ 85°C voltage - Supply (Max) 20mA	Manufacturer Part Number	ECX-L33BN-125.000
Oscillators ackage 6-SMD, No Lead eries ECSpressCON? ECX-L bype XO (Standard) requency 125MHz butput Enable/Disable butput LVDS requency Stability ±50ppm perating Temperature -40°C ~ 85°C butput (Max) 20mA	Manufacturer	ECS Inc.
ackage 6-SMD, No Lead eries ECSpressCON? ECX-L ype XO (Standard) requency 125MHz unction Enable/Disable vuput LVDS voltage - Supply 3.3V perating Temperature -40°C ~ 85°C urrent - Supply (Max) 20mA	Category	Crystals, Oscillators, Resonators
eries ECSpressCON? ECX-L ype XO (Standard) requency 125MHz unction Enable/Disable untut LVDS voltage - Supply 3.3V perating Temperature +40°C ~ 85°C perating Temperature 20mA		Oscillators
ype XO (Standard) requency 125MHz unction Enable/Disable butput LVDS voltage - Supply 3.3V requency Stability ±50ppm operating Temperature -40°C ~ 85°C Supply (Max) 20mA	Package	6-SMD, No Lead
requency 125MHz unction Enable/Disable butput LVDS voltage - Supply 3.3V requency Stability ±50ppm operating Temperature -40°C ~ 85°C operating Supply (Max) 20mA	Series	ECSpressCON? ECX-L
Provide aunctionEnable/DisableDutputLVDSVoltage - Supply3.3Vrequency Stability±50ppmOperating Temperature-40°C ~ 85°CDurrent - Supply (Max)20mA	Туре	XO (Standard)
Dutput LVDS voltage - Supply 3.3V requency Stability ±50pm operating Temperature -40°C ~ 85°C ourrent - Supply (Max) 20mA	Frequency	125MHz
Yoltage - Supply3.3Vrequency Stability±50ppmoperating Temperature-40°C ~ 85°CSurrent - Supply (Max)20mA	Function	Enable/Disable
requency Stability±50ppmoperating Temperature-40°C ~ 85°Courrent - Supply (Max)20mA	Output	LVDS
Operating Temperature-40°C ~ 85°COurrent - Supply (Max)20mA	Voltage - Supply	3.3V
Surrent - Supply (Max) 20mA	Frequency Stability	±50ppm
	Operating Temperature	$-40^{\circ}\text{C} \sim 85^{\circ}\text{C}$
atings -	Current - Supply (Max)	20mA
	Ratings	-
Iounting Type Surface Mount	Mounting Type	Surface Mount
ackage / Case 6-SMD, No Lead	Package / Case	6-SMD, No Lead
ize / Dimension 0.126" L x 0.098" W (3.20mm x 2.50mm)	Size / Dimension	0.126" L x 0.098" W (3.20mm x 2.50mm)
leight - Seated (Max) 0.039" (1.00mm)	Height - Seated (Max)	0.039" (1.00mm)
Report errors?		Report errors?

ECX-L33BN-125.000 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

ECX-L33BN-125.000 Payment Methods



ECX-L33BN-125.000 Shipping Methods



If you have any question about ECX-L33BN-125.000, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com