

EDH226M010A9BAA

EDH226M010A9BAA Information



For Reference Only

Part Number EDH226M010A9BAA

Manufacturer KEMET Category Capacitors

Aluminum Electrolytic Capacitors

Description ALU ELECTROLYTIC SMD EDH 10VDC 4

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EDH226M010A9BAA Specifications

Manufacturer Part Number EDH226M010A9BAA Manufacturer KEMET Category Capacitors Package Radial, Can - SMD Series EDH Capacitance 22µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature 40°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 23mA @ 120Hz Ripple Current - High Frequency 28.75mA @ 10kHz Impedance - Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.222" (5.65mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	*	
CategoryCapacitorsPackageRadial, Can - SMDSeriesEDHCapacitance22µFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency23mA @ 120HzRipple Current - High Frequency28.75mA @ 10kHzImpedance-Lead Spacing-Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.222" (5.65mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Manufacturer Part Number	EDH226M010A9BAA
PackageRadial, Can - SMDSeriesEDHCapacitance22μFTolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency23mA @ 120HzRipple Current - High Frequency28.75mA @ 10kHzImpedance-Lead Spacing-Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.222" (5.65mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Manufacturer	KEMET
Package Radial, Can - SMD Series EDH Capacitance 22µF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 23mA @ 120Hz Ripple Current - High Frequency 28.75mA @ 10kHz Impedance - Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.222" (5.65mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount	Category	Capacitors
Series EDH Capacitance 22μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 23mA @ 120Hz Ripple Current - High Frequency 28.75mA @ 10kHz Impedance - Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.222" (5.65mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount		Aluminum Electrolytic Capacitors
Capacitance 22μF Tolerance ±20% Voltage - Rated 10V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 23mA @ 120Hz Ripple Current - High Frequency 28.75mA @ 10kHz Impedance - Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.222" (5.65mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount	Package	Radial, Can - SMD
Tolerance±20%Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency23mA @ 120HzRipple Current - High Frequency28.75mA @ 10kHzImpedance-Lead Spacing-Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.222" (5.65mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Series	EDH
Voltage - Rated10VESR (Equivalent Series Resistance)-Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-40°C ~ 105°CPolarizationPolarApplicationsAudioRipple Current - Low Frequency23mA @ 120HzRipple Current - High Frequency28.75mA @ 10kHzImpedance-Lead Spacing-Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.222" (5.65mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Capacitance	22μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Polarization Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency 28.75mA @ 120Hz Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type - 2000 Hrs @ 105°C 2000 Hrs @ 105°C -40°C ~ 105°C -40°C	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency Ripple Current - High Frequency 28.75mA @ 120Hz Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 2000 Hrs @ 105°C -40°C ~ 105°C -4	Voltage - Rated	10V
Operating Temperature -40°C ~ 105°C Polarization Polar Applications Audio Ripple Current - Low Frequency 23mA @ 120Hz Ripple Current - High Frequency 28.75mA @ 10kHz Impedance - Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.222" (5.65mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount	ESR (Equivalent Series Resistance)	-
Polarization Polar Applications Audio Ripple Current - Low Frequency 23mA @ 120Hz Ripple Current - High Frequency 28.75mA @ 10kHz Impedance - Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.222" (5.65mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency 28.75mA @ 10kHz Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Audio Audio Audio 23mA @ 120Hz 28.75mA @ 10kHz - 10kHz 10	Operating Temperature	-40°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency 28.75mA @ 10kHz Impedance Lead Spacing - Size / Dimension O.157" Dia (4.00mm) Height - Seated (Max) Surface Mount Land Size O.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount	Polarization	Polar
Ripple Current - High Frequency 28.75mA @ 10kHz Impedance - Lead Spacing - Size / Dimension 0.157" Dia (4.00mm) Height - Seated (Max) 0.222" (5.65mm) Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount	Applications	Audio
Impedance-Lead Spacing-Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.222" (5.65mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Ripple Current - Low Frequency	23mA @ 120Hz
Lead Spacing-Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.222" (5.65mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Ripple Current - High Frequency	28.75mA @ 10kHz
Size / Dimension0.157" Dia (4.00mm)Height - Seated (Max)0.222" (5.65mm)Surface Mount Land Size0.169" L x 0.169" W (4.30mm x 4.30mm)Mounting TypeSurface Mount	Impedance	-
Height - Seated (Max) O.222" (5.65mm) Surface Mount Land Size O.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount	Lead Spacing	-
Surface Mount Land Size 0.169" L x 0.169" W (4.30mm x 4.30mm) Mounting Type Surface Mount	Size / Dimension	0.157" Dia (4.00mm)
Mounting Type Surface Mount	Height - Seated (Max)	0.222" (5.65mm)
	Surface Mount Land Size	0.169" L x 0.169" W (4.30mm x 4.30mm)
Package / Case Radial, Can - SMD	Mounting Type	Surface Mount
	Package / Case	Radial, Can - SMD
Report errors?		Report errors?

EDH226M010A9BAA Guarantees



Ouality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EDH226M010A9BAA Payment Methods



















EDH226M010A9BAA Shipping Methods













If you have any question about EDH226M010A9BAA, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com