

EDN.2M.319.XLN

EDN.2M.319.XLN Information

Heisener.com	Part Number Manufacturer Category Description Package	EDN.2M.319.XLN LEMO Connectors, Interconnects Circular Connectors CONN PNL MNT RCPT 19SKT STR PCB - For the pricing/inventory/lead time, please contact	
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



EDN.2M.319.XLN Specifications

ManufacturerLEMOCategoryConnectors, Interconnects Circular ConnectorsPackage-Package2MConnector TypeReceptacle, Female SocketsNumber of Positions19Shell Size - Insert319Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderOrientationN (Normal)Ingress ProtectionP68 - Dust Tight, WaterproofShell Material, FinishGoldContact FinishSileledYottage - RatedSileledFacturesSileledYottage - RatedSileled		
CategoryConnectors, InterconnectsPackage-Package-Series2MConnector TypeReceptacle, Female SocketsNumber of Positions19Shell Size - Insert319Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN(Normal)Ingress ProtectionH68 - Dust Tight, WaterproofShell Material, FinishGoldContact FinishSicledFastenesShieldedContact FinishAluminum Alloy, Nickel PlatedContact FinishAluminum Alloy, Nickel PlatedFastenesShieldedVoltage - Rated-Current Rating4A	Manufacturer Part Number	EDN.2M.319.XLN
Circular ConnectorsPackage-Series2MConnector TypeReceptacle, Female SocketsNumber of Positions19Shell Size - Insert319Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN(Normal)Ingress ProtectionP68 - Dust Tight, WaterproofShell Material, FinishGoldFeaturesShieldedVoltage - Rated-Current Rating4A	Manufacturer	LEMO
Package-Series2MConnector TypeReceptacle, Female SocketsNumber of Positions19Shell Size - Insert319Shell Size, MIL-Mouting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN(Normal)Ingress ProtectionP68 - Dust Tight, WaterproofShell Material, FinishGoldFeaturesSnieledVoltage - RatedSieledVoltage - RatedSieledVoltage - RatedSieledVoltage - RatedSieledVoltage - RatedAuMaterial FinishSieledVoltage - RatedSieledVoltage - RatedSieledSterent RatingSieledSterent RatingSieledSteren	Category	Connectors, Interconnects
Series2MConnector TypeReceptacle, Female SocketsNumber of Positions19Shell Size - Insert319Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN(Normal)Ingress ProtectionP68 - Dust Tight, WaterproofShell Material, FinishGoldContact FinishShieldedFasturesShieldedVitare RatingAuminum Alloy, Nickel PlatedSoltare RatingShieldedVitaret RatingAlaState RatingShieldedState Rating		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions19Shell Size - Insert319Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN(Normal)Ingress ProtectionHP68 - Dust Tight, WaterproofShell Material, FinishGoldContact FinishGoldVoltage - RatedShieldedVoltage - Rated-Current Rating4A	Package	-
Number of Positions19Shell Size - Insert319Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionP68 - Dust Tight, WaterproofShell Material, FinishGoldContact FinishSiheldedFeaturesShieldedVoltage - Rated-Current Rating4A	Series	2M
Shell Size - Insert319Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishGoldContact FinishShieldedFeaturesShieldedVoltage - Rated-Kurrent Rating4A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL-Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Aurent Rating4A	Number of Positions	19
Mounting TypePanel Mount, Flange; Through HoleTerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionP68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Aurent Rating4A	Shell Size - Insert	319
TerminationSolderFastening TypeThreadedOrientationN (Normal)Ingress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating4A	Shell Size, MIL	-
Fastening TypeThreadedPastening TypeN (Normal)OrientationN (Normal)Ingress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating4A	Mounting Type	Panel Mount, Flange; Through Hole
OrientationN (Normal)Ingress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating4A	Termination	Solder
Ingress ProtectionIP68 - Dust Tight, WaterproofShell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating4A	Fastening Type	Threaded
Shell Material, FinishAluminum Alloy, Nickel PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating4A	Orientation	N (Normal)
Contact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating4A	Ingress Protection	IP68 - Dust Tight, Waterproof
FeaturesShieldedVoltage - Rated-Current Rating4A	Shell Material, Finish	Aluminum Alloy, Nickel Plated
Voltage - Rated-Current Rating4A	Contact Finish	Gold
Current Rating 4A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	4A
		Report errors?

EDN.2M.319.XLN Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

EDN.2M.319.XLN Payment Methods



EDN.2M.319.XLN Shipping Methods



If you have any question about EDN.2M.319.XLN, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com