



### **EE2-9TNUH-L Information**

Part Number EE2-9TNUH-L

Manufacturer KEMET Category Relays

Signal Relays, Up to 2 Amps

RELAY GEN PURPOSE DPDT 2A 9V **Description** 

Package

For the pricing/inventory/lead time, please contact

Website: https://www.heisener.com For Reference Only

E-mail: salesdept@heisener.com



Request a Quote

# **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









## **EE2-9TNUH-L Specifications**

Manufacturer Part Number  KEMET Category Relays Signal Relays, Up to 2 Amps Package - Series EE2 Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 15.6mA Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) Turn Off Voltage (Min) Operate Time Release Time Ims Features Mounting Type Surface Mount Termination Style  KEMET KEMET Relays Signal Relays General Purpose Latching, Du o 2 Amps General Purpose Latching, Dual Coil Coil Campa General Purpose Latching, Dual Coil Coi		
CategoryRelaysPackage-SeriesEE2Relay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current15.6mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage (Max)6.75 VDCTurn On Voltage (Max)-Operate Time2msRelease Time1msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Manufacturer Part Number	EE2-9TNUH-L
Package - Series EE2 Relay Type General Purpose Coil Type Latching, Dual Coil Coil Current 15.6mA Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) - Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style General Purpose General Purpose EE2  EE2  EE2  EE2  EE2  EE2  EE2  EE	Manufacturer	KEMET
Package-SeriesEE2Relay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current15.6mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)-Operate Time2msRelease TimeImsFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Category	Relays
SeriesEE2Relay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current15.6mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)-Operate Time2msRelease TimeImsFeatures-Mounting TypeSurface MountTermination StyleGull Wing		Signal Relays, Up to 2 Amps
Relay TypeGeneral PurposeCoil TypeLatching, Dual CoilCoil Current15.6mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)-Operate Time2msRelease TimeImsFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Package	-
Coil TypeLatching, Dual CoilCoil Current15.6mACoil Voltage9VDCContact FormDPDT (2 Form C)Contact Rating (Current)2ASwitching Voltage250VAC, 220VDC - MaxTurn On Voltage (Max)6.75 VDCTurn Off Voltage (Min)-Operate Time2msRelease TimeImsFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Series	EE2
Coil Current Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) - Operate Time 2ms Release Time Ims Features - Mounting Type Surface Mount Termination Style Gull Wing	Relay Type	General Purpose
Coil Voltage 9VDC Contact Form DPDT (2 Form C) Contact Rating (Current) 2A Switching Voltage 250VAC, 220VDC - Max Turn On Voltage (Max) 6.75 VDC Turn Off Voltage (Min) - Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Coil Type	Latching, Dual Coil
Contact Form DPDT (2 Form C)  Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  6.75 VDC  Turn Off Voltage (Min)  Operate Time  Release Time  Ims  Features  -  Mounting Type  Surface Mount  Termination Style  DPDT (2 Form C)  2A  250VAC, 220VDC - Max  6.75 VDC  -  Unatter of the operator of th	Coil Current	15.6mA
Contact Rating (Current)  Switching Voltage  250VAC, 220VDC - Max  Turn On Voltage (Max)  6.75 VDC  Turn Off Voltage (Min)  Operate Time  2ms  Release Time  1ms  Features  -  Mounting Type  Surface Mount  Termination Style  Gull Wing	Coil Voltage	9VDC
Switching Voltage  Turn On Voltage (Max)  6.75 VDC  Turn Off Voltage (Min)  Operate Time  2ms  Release Time  1ms  Features  -  Mounting Type  Surface Mount  Termination Style  250VAC, 220VDC - Max  6.75 VDC  -  Unit Off Voltage (Min)  -  Surface Mount  Gull Wing	Contact Form	DPDT (2 Form C)
Turn On Voltage (Max)  Turn Off Voltage (Min)  Operate Time  Release Time  Ims  Features  Mounting Type  Surface Mount  Termination Style  6.75 VDC	Contact Rating (Current)	2A
Turn Off Voltage (Min) Operate Time 2ms Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Switching Voltage	250VAC, 220VDC - Max
Operate Time2msRelease Time1msFeatures-Mounting TypeSurface MountTermination StyleGull Wing	Turn On Voltage (Max)	6.75 VDC
Release Time 1ms Features - Mounting Type Surface Mount Termination Style Gull Wing	Turn Off Voltage (Min)	-
Features - Mounting Type Surface Mount Termination Style Gull Wing	Operate Time	2ms
Mounting Type Surface Mount Termination Style Gull Wing	Release Time	1ms
Termination Style Gull Wing	Features	-
	Mounting Type	Surface Mount
Report errors?	Termination Style	Gull Wing
		Report errors?

### **EE2-9TNUH-L Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

# **EE2-9TNUH-L Payment Methods**



















### **EE2-9TNUH-L Shipping Methods**













If you have any question about EE2-9TNUH-L, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com