

EEC30DRTI-S13

est a Quote

EEC30DRTI-S13 Information

Heisener.com	Part Number	EEC30DRTI-S13
	Manufacturer	Sullins Connector Solutions
	Category	Connectors, Interconnects Card Edge Connectors - Edgeboard Connectors
	Description	CONN EDGE DUAL FMALE 60POS 0.100
	Package	-
		For the pricing/inventory/lead time, please contact
For Reference Only		us Website: https://www.heisener.com E-mail: salesdept@heisener.com

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



EEC30DRTI-S13 Specifications

Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions/Bay/Row60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialNosphor BronzeContact Finish Thickness100µin (2.54µm)Contact Finish ThicknessDiolou (2.54µm)Contact TypeBueContact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 125°C		
CategoryConnectors, InterconnectsCard Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions/Bay/Row60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact Finish Thickness100jui (2.54µm)Contact Finish Thickness100jui (2.54µm)Contact TypeFull BellowsContact TypeSolderContact Type100jui (2.54µm)Contact Finish Thickness100jui (2.54µm)Contact TypeFull BellowsContact TypeSolderContact TypeSolde	Manufacturer Part Number	EEC30DRTI-S13
Card Edge Connectors - Edgeboard ConnectorsPackage-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Manufacturer	Sullins Connector Solutions
Package-Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact Material100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Category	Connectors, Interconnects
Series-Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions/Bay/Row60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialNosphor BronzeContact Finish Thickness100µin (2.54µm)Contact Finish ThicknessDiolou (2.54µm)Contact TypeBueContact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-55°C ~ 125°C		Card Edge Connectors - Edgeboard Connectors
Card TypeNon Specified - Dual EdgeGenderFemaleNumber of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountContact MaterialNosphor BronzeContact Finish Thickness100µin (2.54µm)Contact Finish ThicknessTinContact TypeBull BellowsColorBulleFalage FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature65° ~ 125°C	Package	-
GenderFemaleNumber of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeJuloupin (2.54µm)ColorBueFalage FeatureOpmount (2.54µm)Fonge FeatureSolderColorBueFull BellowsSolderFull SeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Series	-
Number of Positions/Bay/Row30Number of Positions60Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact TypeJoluju (2.54µm)ColorBuleFaluge FeatureOpomut Opeming, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Type	Non Specified - Dual Edge
Number of Positions 60 Card Thickness 0.062" (1.57mm) Number of Rows 2 Pitch 0.100" (2.54mm) Features Card Extender Mounting Type Board Edge, Straddle Mount Termination Solder Contact Material Phosphor Bronze Contact Finish Tin Contact Finish Thickness 100µin (2.54µm) Color Full Bellows Color Blue Flange Feature Top Mount Opening, Threaded Insert, 4-40 Operating Temperature -65°C ~ 125°C	Gender	Female
Card Thickness0.062" (1.57mm)Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions/Bay/Row	30
Number of Rows2Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Positions	60
Pitch0.100" (2.54mm)FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Card Thickness	0.062" (1.57mm)
FeaturesCard ExtenderMounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFul BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Number of Rows	2
Mounting TypeBoard Edge, Straddle MountTerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Pitch	0.100" (2.54mm)
TerminationSolderContact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Features	Card Extender
Contact MaterialPhosphor BronzeContact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Mounting Type	Board Edge, Straddle Mount
Contact FinishTinContact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Termination	Solder
Contact Finish Thickness100µin (2.54µm)Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Material	Phosphor Bronze
Contact TypeFull BellowsColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish	Tin
ColorBlueFlange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Finish Thickness	100µin (2.54µm)
Flange FeatureTop Mount Opening, Threaded Insert, 4-40Operating Temperature-65°C ~ 125°C	Contact Type	Full Bellows
Operating Temperature $-65^{\circ}C \sim 125^{\circ}C$	Color	Blue
	Flange Feature	Top Mount Opening, Threaded Insert, 4-40
Report errors?	Operating Temperature	-65°C ~ 125°C
		Report errors?

EEC30DRTI-S13 Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE BUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

EEC30DRTI-S13 Payment Methods



EEC30DRTI-S13 Shipping Methods



If you have any question about EEC30DRTI-S13, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com