



EEE-1HA220WP Information



For Reference Only

Part Number EEE-1HA220WP

Manufacturer Panasonic Electronic Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 22UF 20% 50V SMD

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EEE-1HA220WP Specifications

Manufacturer Part NumberEEE-1HA220WPManufacturerPanasonic Electronic ComponentsCategoryCapacitorsPackageAluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAutomotive, AEC-Q200, SCapacitance22μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency40mA @ 120HzRipple Current - High Frequency68mA @ 10kHz
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series Automotive, AEC-Q200, S Capacitance 22µF Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature 40°C ~ 85°C Polarization Applications Ripple Current - Low Frequency Ripple Current - High Frequency 68mA @ 10kHz
PackageAluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAutomotive, AEC-Q200, SCapacitance22μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency40mA @ 120HzRipple Current - High Frequency68mA @ 10kHz
PackageRadial, Can - SMDSeriesAutomotive, AEC-Q200, SCapacitance22μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency40mA @ 120HzRipple Current - High Frequency68mA @ 10kHz
SeriesAutomotive, AEC-Q200, SCapacitance22μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency40mA @ 120HzRipple Current - High Frequency68mA @ 10kHz
Capacitance22μFTolerance±20%Voltage - Rated50VESR (Equivalent Series Resistance)-Lifetime @ Temp.1000 Hrs @ 85°COperating Temperature-40°C ~ 85°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency40mA @ 120HzRipple Current - High Frequency68mA @ 10kHz
Tolerance ±20% Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 68mA @ 10kHz
Voltage - Rated 50V ESR (Equivalent Series Resistance) - Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 68mA @ 10kHz
ESR (Equivalent Series Resistance) Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 68mA @ 10kHz
Lifetime @ Temp. 1000 Hrs @ 85°C Operating Temperature -40°C ~ 85°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 68mA @ 10kHz
Operating Temperature -40°C ~ 85°C Polarization Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 68mA @ 10kHz
Polarization Polar Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 68mA @ 10kHz
Applications General Purpose Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 68mA @ 10kHz
Ripple Current - Low Frequency 40mA @ 120Hz Ripple Current - High Frequency 68mA @ 10kHz
Ripple Current - High Frequency 68mA @ 10kHz
Impedance -
Lead Spacing -
Size / Dimension 0.248" Dia (6.30mm)
Height - Seated (Max) 0.213" (5.40mm)
Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)
Mounting Type Surface Mount
Package / Case Radial, Can - SMD
Report errors?

EEE-1HA220WP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EEE-1HA220WP Payment Methods



















EEE-1HA220WP Shipping Methods













If you have any question about EEE-1HA220WP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com