



EEE-FK1E391SP Information



For Reference Only

Part Number EEE-FK1E391SP

Manufacturer Panasonic Electronic Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 390UF 20% 25V SMD

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EEE-FK1E391SP Specifications

Manufacturer Part Number Manufacturer Panasonic Electronic Components Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series FKS Capacitance 390µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature Polar Applications Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing - Lead Spacing - Lead Spacing - Size / Dimension Height - Seated (Max) Mounting Type Package / Case Radial Can - SMD	*	
Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series FKS Capacitance 390μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 160 mohm @ 100kHz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Oparating Temperature Automotive Applications Automotive Ripple Current - Low Frequency 390mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount	Manufacturer Part Number	EEE-FK1E391SP
Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series FKS Capacitance 390µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 160 mohm @ 100kHz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency - Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Surface Mount Aduminum Electrolytic Capacitors Radial, Can - SMD Radial, Can - SMD Surface Mount Audina 400 400 400 400 400 400 400 4	Manufacturer	Panasonic Electronic Components
Package Radial, Can - SMD Series FKS Capacitance 390µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 160 mohm @ 100kHz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 390mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount	Category	Capacitors
Series FKS Capacitance 390µF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 160 mohm @ 100kHz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 390mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount		Aluminum Electrolytic Capacitors
Capacitance 390μF Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 160 mohm @ 100kHz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 390mA @ 120Hz Ripple Current - High Frequency - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount	Package	Radial, Can - SMD
Tolerance ±20% Voltage - Rated 25V ESR (Equivalent Series Resistance) 160 mohm @ 100kHz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 390mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount	Series	FKS
Voltage - Rated25VESR (Equivalent Series Resistance)160 mohm @ 100kHzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency390mA @ 120HzRipple Current - High Frequency-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface Mount	Capacitance	390μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 160 mohm @ 100kHz 2000 Hrs @ 105°C -55°C ~ 105°C -105°C -105°C	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -55°C ~ 105°C Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 2000 Hrs @ 105°C -55°C ~ 105°C Automotive Automotive 390mA @ 120Hz - - - - - - - - - - - - -	Voltage - Rated	25V
Operating Temperature -55°C ~ 105°C Polarization Polar Applications Automotive Ripple Current - Low Frequency 390mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount	ESR (Equivalent Series Resistance)	160 mohm @ 100kHz
Polarization Polar Applications Automotive Ripple Current - Low Frequency 390mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount	Lifetime @ Temp.	2000 Hrs @ 105°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Automotive 390mA @ 120Hz - 1000 - 120Hz 1000 - 120H	Operating Temperature	-55°C ~ 105°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type 390mA @ 120Hz - 0.315" Dia (8.00mm) 0.413" (10.50mm) 0.413" (10.50mm) Surface Mount	Polarization	Polar
Ripple Current - High Frequency Impedance	Applications	Automotive
Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount	Ripple Current - Low Frequency	390mA @ 120Hz
Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount	Ripple Current - High Frequency	-
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface Mount	Impedance	-
Height - Seated (Max) O.413" (10.50mm) Surface Mount Land Size O.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount	Lead Spacing	-
Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount	Size / Dimension	0.315" Dia (8.00mm)
Mounting Type Surface Mount	Height - Seated (Max)	0.413" (10.50mm)
	Surface Mount Land Size	0.327" L x 0.327" W (8.30mm x 8.30mm)
Package / Case Radial Can - SMD	Mounting Type	Surface Mount
Tackage / Case	Package / Case	Radial, Can - SMD
Report errors?		Report errors?

EEE-FK1E391SP Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EEE-FK1E391SP Payment Methods



















EEE-FK1E391SP Shipping Methods













If you have any question about EEE-FK1E391SP, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com