

EEE-FP1V101AP

EEE-FP1V101AP Information

	Part Number	EEE-FP1V101AP
VFP.	Manufacturer	Panasonic Electronic Components
	Category	Capacitors Aluminum Electrolytic Capacitors
	Description	CAP ALUM 100UF 20% 35V SMD
	Package	Radial, Can - SMD
		For the pricing/inventory/lead time, please contact us
For Reference Only		Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



EEE-FP1V101AP Specifications

ManufacturerPanasonic Electronic ComponentsCapacitorsCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAutomotive, AEC-Q200, FPCapacitance100µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)80 mOhm @ 100kHzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature55°C ~ 105°CPolarizationPolarApplicationsStotma @ 120HzRipple Current - Low Frequency552.5mA @ 120HzRipple Current - High Frequency550mA @ 100kHzImpedance-Lead Spacing0.315° Dia (8.00mm)Size / Dimension0.402° (10.20mm)Height - Seated (Max)0.327° L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface Mount			
CategoryCapacitorsAluminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAutomotive, AEC-Q200, FPCapacitance100µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)80 mOhm @ 100kHzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency552.5mA @ 120HzRipple Current - High Frequency850mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Manufacturer Part Number	EEE-FP1V101AP	
Auminum Electrolytic CapacitorsPackageRadial, Can - SMDSeriesAutomotive, AEC-Q200, FPCapacitance100µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)80 mOhm @ 100kHzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsStomA @ 120HzRipple Current - Low Frequency552.5mA @ 120HzRipple Current - High Frequency-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Package / CaseRadial, Can - SMD	Manufacturer	Panasonic Electronic Components	
PackageRadial, Can - SMDSeriesAutomotive, AEC-Q20, FPCapacitance100μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)80 mOhm @ 100kHzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsStomA @ 100kHzRipple Current - High Frequency552.5mA @ 120HzImpedance-Lad Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Package / CaseRadial, Can - SMD	Category	Capacitors	
SeriesAutomotive, AEC-Q200, FPCapacitance100µFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)80 mOhm @ 100kHzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency552.5mA @ 120HzRipple Current - High Frequency850mA @ 100kHzImpedance-Lead Spacing0.315" Dia (8.00mm)Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD		Aluminum Electrolytic Capacitors	
Capacitance100μFTolerance±20%Voltage - Rated35VESR (Equivalent Series Resistance)80 mOhm @ 100kHzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency552.5mA @ 120HzImpedance-Lead Spacing0.315" Dia (8.00mm)Size / Dimension0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeRadial, Can - SMD	Package	Radial, Can - SMD	
±20% Yoltage - Rated 35V ESR (Equivalent Series Resistance) 80 mOhm @ 100kHz Lifetime @ Temp. 2000 Hrs @ 105°C Operating Temperature -55°C ~ 105°C Polar Polar Applications Automotive Ripple Current - Low Frequency 552.5mA @ 120Hz Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.402" (10.20mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Series	Automotive, AEC-Q200, FP	
Voltage - Rated35VESR (Equivalent Series Resistance)80 mOhm @ 100kHzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency552.5mA @ 120HzRipple Current - High Frequency850mA @ 100kHzImpedance-Lead Spacing0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeRadial, Can - SMD	Capacitance	100µF	
Constraint80 mOhm @ 100kHzESR (Equivalent Series Resistance)80 mOhm @ 100kHzLifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency552.5mA @ 120HzBipple Current - High Frequency850mA @ 100kHzImpedance-Lead Spacing0.315" Dia (8.00mm)Size / Dimension0.402" (10.20mm)Height - Seated (Max)0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Tolerance	±20%	
Lifetime @ Temp.2000 Hrs @ 105°COperating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency552.5mA @ 120HzRipple Current - High Frequency850mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Voltage - Rated	35V	
Operating Temperature-55°C ~ 105°CPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency552.5mA @ 120HzRipple Current - High Frequency850mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.327" L x 0.327" W (8.30mm x 8.30mm)Surface Mount Land SizeSurface MountMounting TypeRadial, Can - SMD	ESR (Equivalent Series Resistance)	80 mOhm @ 100kHz	
PolarizationPolarPolarizationPolarApplicationsAutomotiveRipple Current - Low Frequency552.5mA @ 120HzRipple Current - High Frequency850mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Lifetime @ Temp.	2000 Hrs @ 105°C	
ApplicationsAutomotiveRipple Current - Low Frequency552.5mA @ 120HzRipple Current - High Frequency850mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Operating Temperature	-55°C ~ 105°C	
Ripple Current - Low Frequency552.5mA @ 120HzRipple Current - High Frequency850mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Polarization	Polar	
Ripple Current - High Frequency850mA @ 100kHzImpedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Applications	Automotive	
Impedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Ripple Current - Low Frequency	552.5mA @ 120Hz	
Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Ripple Current - High Frequency	850mA @ 100kHz	
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Impedance	-	
Height - Seated (Max)0.402" (10.20mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Lead Spacing	-	
Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Size / Dimension	0.315" Dia (8.00mm)	
Mounting Type Surface Mount Package / Case Radial, Can - SMD	Height - Seated (Max)	0.402" (10.20mm)	
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.327" L x 0.327" W (8.30mm x 8.30mm)	
	Mounting Type	Surface Mount	
Report errors?	Package / Case	Radial, Can - SMD	
			Report errors?

EEE-FP1V101AP Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

EEE-FP1V101AP Payment Methods



EEE-FP1V101AP Shipping Methods



If you have any question about EEE-FP1V101AP, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com