



### **EEE-HB0J101P Information**



For Reference Only

Part Number EEE-HB0J101P

Manufacturer Panasonic Electronic Components

**Category** Capacitors

**Aluminum Electrolytic Capacitors** 

**Description** CAP ALUM 100UF 20% 6.3V SMD

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

### **Certified Quality**

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









# **EEE-HB0J101P Specifications**

Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - SMD           Series         Automotive, AEC-Q200, HB           Capacitance         100μF           Tolerance         ±20%           Voltage - Rated         6.3V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         Automotive           Ripple Current - Low Frequency         71mA @ 120Hz           Ripple Current - High Frequency         120.7mA @ 10kHz           Impedance         -           Lead Spacing         -           Size / Dimension         0.248" Dia (6.30mm)           Height - Seated (Max)         0.228" (5.80mm)           Surface Mount Land Size         0.260" L x 0.260" W (6.60mm x 6.60mm)			
Category         Capacitors           Aluminum Electrolytic Capacitors           Package         Radial, Can - SMD           Series         Automotive, AEC-Q200, HB           Capacitance         100µF           Tolerance         ±20%           Voltage - Rated         6.3V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         Automotive           Ripple Current - Low Frequency         71mA @ 120Hz           Ripple Current - High Frequency         120.7mA @ 10kHz           Impedance         -           Lead Spacing         -           Size / Dimension         0.248" Dia (6.30mm)           Height - Seated (Max)         0.228" (5.80mm)           Surface Mount Land Size         0.260" L x 0.260" W (6.60mm x 6.60mm)           Mounting Type         Surface Mount           Package / Case         Radial, Can - SMD	Manufacturer Part Number	EEE-HB0J101P	
Aluminum Electrolytic Capacitors	Manufacturer	Panasonic Electronic Components	
Package         Radial, Can - SMD           Series         Automotive, AEC-Q200, HB           Capacitance         100μF           Tolerance         ±20%           Voltage - Rated         6.3V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         Automotive           Ripple Current - Low Frequency         71mA @ 120Hz           Ripple Current - High Frequency         120.7mA @ 10kHz           Impedance         -           Lead Spacing         -           Size / Dimension         0.248" Dia (6.30mm)           Height - Seated (Max)         0.228" (5.80mm)           Surface Mount Land Size         0.260" L x 0.260" W (6.60mm x 6.60mm)           Mounting Type         Surface Mount           Package / Case         Radial, Can - SMD	Category	Capacitors	
Series         Automotive, AEC-Q200, HB           Capacitance         100µF           Tolerance         ±20%           Voltage - Rated         6.3V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         Automotive           Ripple Current - Low Frequency         71mA @ 120Hz           Ripple Current - High Frequency         120.7mA @ 10kHz           Impedance         -           Lead Spacing         -           Size / Dimension         0.248" Dia (6.30mm)           Height - Seated (Max)         0.228" (5.80mm)           Surface Mount Land Size         0.260" L x 0.260" W (6.60mm x 6.60mm)           Mounting Type         Surface Mount           Package / Case         Radial, Can - SMD		Aluminum Electrolytic Capacitors	
Capacitance         100μF           Tolerance         ±20%           Voltage - Rated         6.3V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         Automotive           Ripple Current - Low Frequency         71mA @ 120Hz           Ripple Current - High Frequency         120.7mA @ 10kHz           Impedance         -           Lead Spacing         -           Size / Dimension         0.248" Dia (6.30mm)           Height - Seated (Max)         0.228" (5.80mm)           Surface Mount Land Size         0.260" L x 0.260" W (6.60mm x 6.60mm)           Mounting Type         Surface Mount           Package / Case         Radial, Can - SMD	Package	Radial, Can - SMD	
Tolerance         ±20%           Voltage - Rated         6.3V           ESR (Equivalent Series Resistance)         -           Lifetime @ Temp.         2000 Hrs @ 105°C           Operating Temperature         -40°C ~ 105°C           Polarization         Polar           Applications         Automotive           Ripple Current - Low Frequency         71mA @ 120Hz           Ripple Current - High Frequency         120.7mA @ 10kHz           Impedance         -           Lead Spacing         -           Size / Dimension         0.248" Dia (6.30mm)           Height - Seated (Max)         0.228" (5.80mm)           Surface Mount Land Size         0.260" L x 0.260" W (6.60mm x 6.60mm)           Mounting Type         Surface Mount           Package / Case         Radial, Can - SMD	Series	Automotive, AEC-Q200, HB	
Voltage - Rated  ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  -40°C ~ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  Automotive  Ripple Current - Low Frequency  Ripple Current - High Frequency  120.7mA @ 120Hz  Impedance  -  Lead Spacing  -  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  0.260" L x 0.260" W (6.60mm x 6.60mm)  Mounting Type  Surface Mount  Package / Case  Radial, Can - SMD	Capacitance	100μF	
ESR (Equivalent Series Resistance)  Lifetime @ Temp.  2000 Hrs @ 105°C  Operating Temperature  -40°C ~ 105°C  Polarization  Applications  Automotive  Ripple Current - Low Frequency  Ripple Current - High Frequency  120.7mA @ 120Hz  Impedance  -  Lead Spacing  Size / Dimension  0.248" Dia (6.30mm)  Height - Seated (Max)  Surface Mount Land Size  0.260" L x 0.260" W (6.60mm x 6.60mm)  Mounting Type  Surface Mount  Package / Case  Radial, Can - SMD	Tolerance	±20%	
Lifetime @ Temp.  Operating Temperature  -40°C ~ 105°C  Polarization  Polar  Applications  Automotive  Ripple Current - Low Frequency  Ripple Current - High Frequency  120.7mA @ 120Hz  Impedance  -  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  2000 Hrs @ 105°C  -40°C ~	Voltage - Rated	6.3V	
Operating Temperature  -40°C ~ 105°C  Polarization  Applications  Automotive  Ripple Current - Low Frequency  Ripple Current - High Frequency  120.7mA @ 120Hz  Impedance  - Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  -40°C ~ 105°C  Polar  -40°C ~ 105°C  -40°C ~ 105	ESR (Equivalent Series Resistance)	-	
Polarization Applications Automotive Ripple Current - Low Frequency Ripple Current - High Frequency Ripple Current - Low Frequency Ripple Current -	Lifetime @ Temp.	2000 Hrs @ 105°C	
Applications  Ripple Current - Low Frequency  Ripple Current - High Frequency  Ripple Current - High Frequency  120.7mA @ 10kHz  Impedance  - Lead Spacing  - Size / Dimension  0.248" Dia (6.30mm)  Height - Seated (Max)  0.228" (5.80mm)  Surface Mount Land Size  0.260" L x 0.260" W (6.60mm x 6.60mm)  Mounting Type  Surface Mount  Package / Case  Radial, Can - SMD	Operating Temperature	-40°C ~ 105°C	
Ripple Current - Low Frequency  Ripple Current - High Frequency  120.7mA @ 10kHz  Impedance  - Lead Spacing  - Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Surface Mount  Package / Case  71mA @ 120Hz  71mA @ 120Hz  71mA @ 120Hz  71mA @ 120Hz  120.7mA @ 10kHz  -  0.248" Dia (6.30mm)  0.248" Dia (6.30mm)  0.228" (5.80mm)  Surface Mount  Radial, Can - SMD	Polarization	Polar	
Ripple Current - High Frequency  Impedance  Lead Spacing  Size / Dimension  Height - Seated (Max)  Surface Mount Land Size  Mounting Type  Package / Case  120.7mA @ 10kHz  -  120.7ma	Applications	Automotive	
Impedance         -           Lead Spacing         -           Size / Dimension         0.248" Dia (6.30mm)           Height - Seated (Max)         0.228" (5.80mm)           Surface Mount Land Size         0.260" L x 0.260" W (6.60mm x 6.60mm)           Mounting Type         Surface Mount           Package / Case         Radial, Can - SMD	Ripple Current - Low Frequency	71mA @ 120Hz	
Lead Spacing         -           Size / Dimension         0.248" Dia (6.30mm)           Height - Seated (Max)         0.228" (5.80mm)           Surface Mount Land Size         0.260" L x 0.260" W (6.60mm x 6.60mm)           Mounting Type         Surface Mount           Package / Case         Radial, Can - SMD	Ripple Current - High Frequency	120.7mA @ 10kHz	
Size / Dimension 0.248" Dia (6.30mm)  Height - Seated (Max) 0.228" (5.80mm)  Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)  Mounting Type Surface Mount  Package / Case Radial, Can - SMD	Impedance	-	
Height - Seated (Max)  Surface Mount Land Size  0.228" (5.80mm)  0.260" L x 0.260" W (6.60mm x 6.60mm)  Mounting Type  Surface Mount  Package / Case  Radial, Can - SMD	Lead Spacing	-	
Surface Mount Land Size 0.260" L x 0.260" W (6.60mm x 6.60mm)  Mounting Type Surface Mount  Package / Case Radial, Can - SMD	Size / Dimension	0.248" Dia (6.30mm)	
Mounting Type Surface Mount Package / Case Radial, Can - SMD	Height - Seated (Max)	0.228" (5.80mm)	
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.260" L x 0.260" W (6.60mm x 6.60mm)	
	Mounting Type	Surface Mount	
Report errors?	Package / Case	Radial, Can - SMD	
•			Report errors?

#### **EEE-HB0J101P Guarantees**



### **Quality Guarantees**

We provide 90 days warranty. \*

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



#### **Service Guarantees**

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

### **EEE-HB0J101P Payment Methods**



















## **EEE-HB0J101P Shipping Methods**













If you have any question about EEE-HB0J101P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com