



EEE-TC1V470P Information

www.heisener.com

For Reference Only

Part Number EEE-TC1V470P

Manufacturer Panasonic Electronic Components

Category Capacitors

Aluminum Electrolytic Capacitors

Description CAP ALUM 47UF 20% 35V SMD

Package Radial, Can - SMD

For the pricing/inventory/lead time, please contact

us

Website: https://www.heisener.com E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EEE-TC1V470P Specifications

Manufacturer Part Number EEE-TC1V470P Manufacturer Panasonic Electronic Components Category Capacitors Aluminum Electrolytic Capacitors Package Radial, Can - SMD Series TC Capacitance 47µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 200 mOhm @ 100kHz Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 266.5mA @ 120Hz Ripple Current - High Frequency - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" Lx 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	1	
Category Capacitors Package Radial, Can - SMD Series TC Capacitance 47μF Tolerance ±20% Voltage - Rated 35 V ESR (Equivalent Series Resistance) 200 mOhm @ 100kHz Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 266.5mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer Part Number	EEE-TC1V470P
Package Radial, Can - SMD Series TC Capacitance 47μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 200 mOhm @ 100kHz Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 266.5mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Manufacturer	Panasonic Electronic Components
Package Radial, Can - SMD Series TC Capacitance 47µF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 200 mOhm @ 100kHz Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 266.5mA @ 120Hz Ripple Current - High Frequency - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Category	Capacitors
Series TC Capacitance 47μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 200 mOhm @ 100kHz Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 266.5mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD		Aluminum Electrolytic Capacitors
Capacitance 47μF Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 200 mOhm @ 100kHz Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 266.5mA @ 120Hz Ripple Current - High Frequency - Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Package	Radial, Can - SMD
Tolerance ±20% Voltage - Rated 35V ESR (Equivalent Series Resistance) 200 mOhm @ 100kHz Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency 266.5mA @ 120Hz Ripple Current - High Frequency - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Series	TC
Voltage - Rated35VESR (Equivalent Series Resistance)200 mOhm @ 100kHzLifetime @ Temp.3000 Hrs @ 125°COperating Temperature-40°C ~ 125°CPolarizationPolarApplicationsGeneral PurposeRipple Current - Low Frequency266.5mA @ 120HzRipple Current - High Frequency-Impedance-Lead Spacing-Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Capacitance	47μF
ESR (Equivalent Series Resistance) Lifetime @ Temp. 3000 Hrs @ 125°C Operating Temperature -40°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency 266.5mA @ 120Hz Ripple Current - High Frequency - Impedance Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Tolerance	±20%
Lifetime @ Temp. Operating Temperature -40°C ~ 125°C Polarization Polar Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Oaklar Surface Mount Package / Case Ripple Current - High Frequency - Lad Spacing - Surface Mount Surface Mount Surface Mount Radial, Can - SMD	Voltage - Rated	35V
Operating Temperature -40°C ~ 125°C Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Polar -40°C ~ 125°C Polar General Purpose 266.5mA @ 120Hz - - - - - - - - - - - - -	ESR (Equivalent Series Resistance)	200 mOhm @ 100kHz
Polarization Applications General Purpose Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Page 120Hz 266.5mA @ 120Hz	Lifetime @ Temp.	3000 Hrs @ 125°C
Applications Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case Ripple Current - Low Frequency - 266.5mA @ 120Hz - 100.5mm (100.5mm) - 100.315" Dia (8.00mm) 0.413" (10.50mm) 0.413" (10.50mm) Surface Mount Land Size Radial, Can - SMD	Operating Temperature	-40°C ~ 125°C
Ripple Current - Low Frequency Ripple Current - High Frequency Impedance Lead Spacing Size / Dimension Height - Seated (Max) Surface Mount Land Size Mounting Type Package / Case 266.5mA @ 120Hz - 266.5mA @ 120Hz	Polarization	Polar
Ripple Current - High Frequency Impedance Lead Spacing - Size / Dimension Height - Seated (Max) Surface Mount Land Size O.315" Dia (8.00mm) 0.413" (10.50mm) Surface Mount Land Size Surface Mount Land Size Surface Mount Radial, Can - SMD	Applications	General Purpose
Impedance - Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - Low Frequency	266.5mA @ 120Hz
Lead Spacing - Size / Dimension 0.315" Dia (8.00mm) Height - Seated (Max) 0.413" (10.50mm) Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Ripple Current - High Frequency	-
Size / Dimension0.315" Dia (8.00mm)Height - Seated (Max)0.413" (10.50mm)Surface Mount Land Size0.327" L x 0.327" W (8.30mm x 8.30mm)Mounting TypeSurface MountPackage / CaseRadial, Can - SMD	Impedance	-
Height - Seated (Max) Surface Mount Land Size 0.413" (10.50mm) 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Lead Spacing	-
Surface Mount Land Size 0.327" L x 0.327" W (8.30mm x 8.30mm) Mounting Type Surface Mount Package / Case Radial, Can - SMD	Size / Dimension	0.315" Dia (8.00mm)
Mounting Type Surface Mount Package / Case Radial, Can - SMD	Height - Seated (Max)	0.413" (10.50mm)
Package / Case Radial, Can - SMD	Surface Mount Land Size	0.327" L x 0.327" W (8.30mm x 8.30mm)
	Mounting Type	Surface Mount
Report errors?	Package / Case	Radial, Can - SMD
		Report errors?

EEE-TC1V470P Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EEE-TC1V470P Payment Methods



















EEE-TC1V470P Shipping Methods













If you have any question about EEE-TC1V470P, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com