

EEF-UD0D331XE

EEF-UD0D331XE Information

www.helsener.com	Part Number Manufacturer Category Description Package	EEF-UD0D331XE Panasonic Electronic Components Capacitors Aluminum - Polymer Capacitors CAP ALUM POLY 330UF 20% 2V SMD 2917 (7343 Metric)	
For Reference Only	Package	For the pricing/inventory/lead time, please contact us Website: https://www.heisener.com E-mail: salesdept@heisener.com	Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.



EEF-UD0D331XE Specifications

Manufacturer Panasonic Electronic Components Category Capacitors Aluminum - Polymer Capacitors 2917 (7343 Metric) Package 2917 (7343 Metric) Series SP-Cap UD Type Polymer Capacitors 30µF Capacitance ±20% Voltage - Rated 2V ESR (Equivalent Series Resistance) 12 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency -33A @ 100kHz Impedance - Lied Spacing 0.287" L x 0.169" W (7.30mm x 4.30mm) Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Mounting Type Surface Mount Land Size		
CategoryCapacitorsAluminum - Polymer CapacitorsPackage2917 (7343 Metric)Package2917 (7343 Metric)SeriesSP-Cap UDTypePolymerCapacitance330µFColarance±20%Voltage - Rated2VESR (Equivalent Series Resistance)12 mOhmLifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency3.3A @ 100kHzImpedance-Lief Staciel (Max)0.110° (2.80mm)Surface Mount Land Size0.287" L x 0.169" W (7.30mm x 4.30mm)Mounting TypeSurface MountPackage / Case2917 (7343 Metric)	Manufacturer Part Number	EEF-UD0D331XE
Aluminum - Polymer CapacitorsPackage2917 (7343 Metric)SeriesSP-Cap UDTypePolymerCapacitance330µFTolerance±20%Voltage - Rated2VESR (Equivalent Series Resistance)12 mOhmLifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.110" (2.80mm)Surface Mount Land Size0.287" L x 0.169" W (7.30mm x 4.30mm)Package / Case2917 (7343 Metric)	Manufacturer	Panasonic Electronic Components
Package2917 (7343 Metric)SeriesSP-Cap UDTypePolymerCapacitance330µFTolerance±20%Voltage - Rated2VESR (Equivalent Series Resistance)12 mOhmLifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency-Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.10" (2.80mm)Surface Mount Land Size0.287" L x 0.169" W (7.30mm x 4.30mm)Package / Case2917 (7343 Metric)	Category	Capacitors
SeriesSP-Cap UDTypePolymerCapacitance330µFTolerance±20%Voltage - Rated2VESR (Equivalent Series Resistance)12 mOhmLifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CApplicationsGeneral PurposeRipple Current - High Frequency-Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.287" L x 0.169" W (7.30mm x 4.30mm)Surface Mount Land Size0.287" L x 0.169" W (7.30mm x 4.30mm)Package / Case2917 (7343 Metric)		Aluminum - Polymer Capacitors
Type Polymer Capacitance 330µF Tolerance ±20% Voltage - Rated 2V ESR (Equivalent Series Resistance) 12 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature 40°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Lifedance - Lised Spacing - Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.287" L x 0.169" W (7.30mm x 4.30mm) Surface Mount Land Size 0.287" L x 0.169" W (7.30mm x 4.30mm) Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Package	2917 (7343 Metric)
Capacitance 330µF Tolerance ±20% Voltage - Rated 2V ESR (Equivalent Series Resistance) 12 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 3.3A @ 100kHz Innedance - Lied Spacing - Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.110" (2.80mm) Surface Mount Land Size 0.287" L x 0.169" W (7.30mm x 4.30mm) Package / Case 2917 (7343 Metric)	Series	SP-Cap UD
$\pm 20\%$ Tolerance $\pm 20\%$ Voltage - Rated $2V$ ESR (Equivalent Series Resistance) 12 mOhm Lifetime @ Temp. $1000 \text{ Hrs @ } 105^{\circ}\text{C}$ Operating Temperature $-40^{\circ}\text{C} \sim 105^{\circ}\text{C}$ ApplicationsGeneral PurposeRipple Current - Low Frequency $-$ Ripple Current - High Frequency $3.3A @ 100 \text{ Hz}$ Impedance $-$ Lead Spacing $0.287" \text{ L x } 0.169" W (7.30 \text{ mm x } 4.30 \text{ mm})$ Height - Seated (Max) $0.110" (2.80 \text{ mm})$ Surface Mount Land Size $0.287" \text{ L x } 0.169" W (7.30 \text{ mm x } 4.30 \text{ mm})$ Mounting TypeSurface MountPackage / Case $2917 (7343 \text{ Metric})$	Туре	Polymer
Voltage - Rated 2V ESR (Equivalent Series Resistance) 12 mOhm Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 3.3A @ 100kHz Impedance - Lead Spacing 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.287" L x 0.169" W (7.30mm x 4.30mm) Surface Mount Land Size 0.287" L x 0.169" W (7.30mm x 4.30mm) Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Capacitance	330µF
ESR (Equivalent Series Resistance)12 mOhmLifetime @ Temp.1000 Hrs @ 105°COperating Temperature-40°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency3.3A @ 100kHzImpedance-Lead Spacing-Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.110" (2.80mm)Surface Mount Land Size0.287" L x 0.169" W (7.30mm x 4.30mm)Mounting TypeSurface MountPackage / Case2917 (7343 Metric)	Tolerance	±20%
Lifetime @ Temp. 1000 Hrs @ 105°C Operating Temperature -40°C ~ 105°C Applications General Purpose Ripple Current - Low Frequency - Ripple Current - High Frequency 3.3A @ 100kHz Impedance - Lead Spacing - Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.110" (2.80mm) Surface Mount Land Size 0.287" L x 0.169" W (7.30mm x 4.30mm) Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Voltage - Rated	2V
Operating Temperature-40°C ~ 105°CApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency3.3A @ 100kHzImpedance-Lead Spacing-Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.110" (2.80mm)Surface Mount Land Size0.287" L x 0.169" W (7.30mm x 4.30mm)Mounting TypeSurface MountPackage / Case2917 (7343 Metric)	ESR (Equivalent Series Resistance)	12 mOhm
ApplicationsGeneral PurposeRipple Current - Low Frequency-Ripple Current - High Frequency3.3A @ 100kHzImpedance-Lead Spacing-Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.110" (2.80mm)Surface Mount Land Size0.287" L x 0.169" W (7.30mm x 4.30mm)Mounting TypeSurface MountPackage / Case2917 (7343 Metric)	Lifetime @ Temp.	1000 Hrs @ 105°C
Ripple Current - Low Frequency-Ripple Current - High Frequency3.3A @ 100kHzImpedance-Lead Spacing-Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.110" (2.80mm)Surface Mount Land Size0.287" L x 0.169" W (7.30mm x 4.30mm)Mounting TypeSurface MountPackage / Case2917 (7343 Metric)	Operating Temperature	-40°C ~ 105°C
Ripple Current - High Frequency3.3A @ 100kHzImpedance-Lead Spacing-Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.110" (2.80mm)Surface Mount Land Size0.287" L x 0.169" W (7.30mm x 4.30mm)Mounting TypeSurface MountPackage / Case2917 (7343 Metric)	Applications	General Purpose
Impedance-Lead Spacing-Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.110" (2.80mm)Surface Mount Land Size0.287" L x 0.169" W (7.30mm x 4.30mm)Mounting TypeSurface MountPackage / Case2917 (7343 Metric)	Ripple Current - Low Frequency	-
Lead Spacing-Size / Dimension0.287" L x 0.169" W (7.30mm x 4.30mm)Height - Seated (Max)0.110" (2.80mm)Surface Mount Land Size0.287" L x 0.169" W (7.30mm x 4.30mm)Mounting TypeSurface MountPackage / Case2917 (7343 Metric)	Ripple Current - High Frequency	3.3A @ 100kHz
Size / Dimension 0.287" L x 0.169" W (7.30mm x 4.30mm) Height - Seated (Max) 0.110" (2.80mm) Surface Mount Land Size 0.287" L x 0.169" W (7.30mm x 4.30mm) Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Impedance	-
Height - Seated (Max)0.110" (2.80mm)Surface Mount Land Size0.287" L x 0.169" W (7.30mm x 4.30mm)Mounting TypeSurface MountPackage / Case2917 (7343 Metric)	Lead Spacing	-
Surface Mount Land Size0.287" L x 0.169" W (7.30mm x 4.30mm)Mounting TypeSurface MountPackage / Case2917 (7343 Metric)	Size / Dimension	0.287" L x 0.169" W (7.30mm x 4.30mm)
Mounting Type Surface Mount Package / Case 2917 (7343 Metric)	Height - Seated (Max)	0.110" (2.80mm)
Package / Case 2917 (7343 Metric)	Surface Mount Land Size	0.287" L x 0.169" W (7.30mm x 4.30mm)
	Mounting Type	Surface Mount
Report errors?	Package / Case	2917 (7343 Metric)
		Report errors

EEF-UD0D331XE Guarantees



Quality Guarantees

We provide 90 days warranty. * If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.

SERVICE EUARANTEE

Service Guarantees

We guarantee 100% customer satisfaction. Our experienced sales team and tech support team back our services to satisfy all our customers.

EEF-UD0D331XE Payment Methods



EEF-UD0D331XE Shipping Methods



If you have any question about EEF-UD0D331XE, please do not hesitate to contact us! Website: https://www.heisener.com E-mail: salesdept@heisener.com