



EEG.1K.302.CLL Information

Heisener.com

Part Number EEG.1K.302.CLL

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description CONN PNL MNT RCPT 2SKT SLD CUP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EEG.1K.302.CLL Specifications

Manufacturer Part Number EEG.1K.302.CLL Manufacturer LEMO Category Connectors, Interconnects Package - Series 1K Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 302 Shell Size, MIL - Mounting Type Panel Mount, Flange - Front Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 15A		
CategoryConnectors, InterconnectsPackage-Series1 KConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating15A	Manufacturer Part Number	EEG.1K.302.CLL
Package - Series IK Connector Type Receptacle, Female Sockets Number of Positions 2 Shell Size - Insert 302 Shell Size, MIL - Mounting Type Panel Mount, Flange - Front Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Gold Features Shielded Voltage - Rated Current Rating 15A	Manufacturer	LEMO
Package-Series1KConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress Protection1P66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating15A	Category	Connectors, Interconnects
Series1KConnector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating15A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating15A	Package	-
Number of Positions2Shell Size - Insert302Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating15A	Series	1K
Shell Size - Insert 302 Shell Size, MIL - Mounting Type Panel Mount, Flange - Front Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 15A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange - Front Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 15A	Number of Positions	2
Mounting TypePanel Mount, Flange - Front Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating15A	Shell Size - Insert	302
Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 15A	Shell Size, MIL	-
Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 15A	Mounting Type	Panel Mount, Flange - Front Side Nut
Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 15A	Termination	Solder Cup
Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 15A	Fastening Type	Push-Pull, Detent Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 15A	Orientation	G
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 15A	Ingress Protection	IP66/68 - Dust Tight, Water Resistant, Waterproof
Features Shielded Voltage - Rated - Current Rating 15A	Shell Material, Finish	Brass, Chrome Plated
Voltage - Rated - Current Rating 15A	Contact Finish	Gold
Current Rating 15A	Features	Shielded
-	Voltage - Rated	-
Report errors?	Current Rating	15A
*		Report errors?

EEG.1K.302.CLL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EEG.1K.302.CLL Payment Methods



















EEG.1K.302.CLL Shipping Methods













If you have any question about EEG.1K.302.CLL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com