



EEG.2K.326.CLL Information

Heisener.com

Part Number EEG.2K.326.CLL

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description CONN PNL MNT RCPT 26SKT SLD CUP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EEG.2K.326.CLL Specifications

| Manufacturer Part Number EEG.2K.326.CLL Manufacturer LEMO Category Connectors, Interconnects Package - Series 2K Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert 326 Shell Size, MIL - Mounting Type Panel Mount, Flange - Front Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 2A | | | |
|--|--------------------------|---|------|
| CategoryConnectors, InterconnectsPackage-Series2KConnector TypeReceptacle, Female SocketsNumber of Positions26Shell Size - Insert326Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating2A | Manufacturer Part Number | EEG.2K.326.CLL | |
| Package - Series 2K Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert 326 Shell Size, MIL - Mounting Type Panel Mount, Flange - Front Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Gold Features Shielded Voltage - Rated Current Rating 2A | Manufacturer | LEMO | |
| Package-Series2KConnector TypeReceptacle, Female SocketsNumber of Positions26Shell Size - Insert326Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating2A | Category | Connectors, Interconnects | |
| Series 2K Connector Type Receptacle, Female Sockets Number of Positions 26 Shell Size - Insert 326 Shell Size, MIL - Mounting Type Panel Mount, Flange - Front Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated Current Rating 2A | | Circular Connectors | |
| Connector TypeReceptacle, Female SocketsNumber of Positions26Shell Size - Insert326Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating2A | Package | - | |
| Number of Positions26Shell Size - Insert326Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating2A | Series | 2K | |
| Shell Size - Insert 326 Shell Size, MIL - Mounting Type Panel Mount, Flange - Front Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 2A | Connector Type | Receptacle, Female Sockets | |
| Shell Size, MIL Mounting Type Panel Mount, Flange - Front Side Nut Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 2A | Number of Positions | 26 | |
| Mounting TypePanel Mount, Flange - Front Side NutTerminationSolder CupFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating2A | Shell Size - Insert | 326 | |
| Termination Solder Cup Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 2A | Shell Size, MIL | - | |
| Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 2A | Mounting Type | Panel Mount, Flange - Front Side Nut | |
| Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 2A | Termination | Solder Cup | |
| Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 2A | Fastening Type | Push-Pull, Detent Lock | |
| Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 2A | Orientation | G | |
| Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 2A | Ingress Protection | IP66/68 - Dust Tight, Water Resistant, Waterproof | |
| Features Shielded Voltage - Rated - Current Rating 2A | Shell Material, Finish | Brass, Chrome Plated | |
| Voltage - Rated - Current Rating 2A | Contact Finish | Gold | |
| Current Rating 2A | Features | Shielded | |
| - | Voltage - Rated | - | |
| Domont owners? | Current Rating | 2A | |
| Report errors? | | Report error | ors? |

EEG.2K.326.CLL Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EEG.2K.326.CLL Payment Methods



















EEG.2K.326.CLL Shipping Methods













If you have any question about EEG.2K.326.CLL, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com