



EEG.3K.305.CYM Information

Heisener.com

Part Number EEG.3K.305.CYM

Manufacturer LEMO

Category Connectors, Interconnects

Circular Connectors

Description CONN RCPT 5POS PNL MNT SKT CRMP

Package -

For the pricing/inventory/lead time, please contact

us

For Reference Only Website: https://www.heisener.com

E-mail: salesdept@heisener.com



Request a Quote

Certified Quality

Heisener's commitment to quality has shaped our processes for sourcing, testing, shipping, and every step in between. This foundation underlies each component we sell.









EEG.3K.305.CYM Specifications

Manufacturer Part Number EEG.3K.305.CYM Manufacturer LEMO Category Connectors, Interconnects Package - Series 3K Connector Type Receptacle, Female Sockets Number of Positions 5 Shell Size - Insert 305 Shell Size, MIL - Mounting Type Panel Mount, Flange - Front Side Nut Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 19A		
CategoryConnectors, InterconnectsPackage-Series3KConnector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert305Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating19A	Manufacturer Part Number	EEG.3K.305.CYM
Package-Series3KConnector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert305Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating19A	Manufacturer	LEMO
Package-Series3KConnector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert305Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating19A	Category	Connectors, Interconnects
Series3KConnector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert305Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating19A		Circular Connectors
Connector TypeReceptacle, Female SocketsNumber of Positions5Shell Size - Insert305Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating19A	Package	-
Number of Positions5Shell Size - Insert305Shell Size, MIL-Mounting TypePanel Mount, Flange - Front Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating19A	Series	3K
Shell Size - Insert 305 Shell Size, MIL - Mounting Type Panel Mount, Flange - Front Side Nut Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 19A	Connector Type	Receptacle, Female Sockets
Shell Size, MIL Mounting Type Panel Mount, Flange - Front Side Nut Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 19A	Number of Positions	5
Mounting TypePanel Mount, Flange - Front Side NutTerminationCrimpFastening TypePush-Pull, Detent LockOrientationGIngress ProtectionIP66/68 - Dust Tight, Water Resistant, WaterproofShell Material, FinishBrass, Chrome PlatedContact FinishGoldFeaturesShieldedVoltage - Rated-Current Rating19A	Shell Size - Insert	305
Termination Crimp Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 19A	Shell Size, MIL	-
Fastening Type Push-Pull, Detent Lock Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 19A	Mounting Type	Panel Mount, Flange - Front Side Nut
Orientation G Ingress Protection IP66/68 - Dust Tight, Water Resistant, Waterproof Shell Material, Finish Brass, Chrome Plated Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 19A	Termination	Crimp
Ingress Protection Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating IP66/68 - Dust Tight, Water Resistant, Waterproof Brass, Chrome Plated Gold Shielded	Fastening Type	Push-Pull, Detent Lock
Shell Material, Finish Contact Finish Gold Features Shielded Voltage - Rated Current Rating 19A	Orientation	G
Contact Finish Gold Features Shielded Voltage - Rated - Current Rating 19A	Ingress Protection	IP66/68 - Dust Tight, Water Resistant, Waterproof
Features Shielded Voltage - Rated - Current Rating 19A	Shell Material, Finish	Brass, Chrome Plated
Voltage - Rated - Current Rating 19A	Contact Finish	Gold
Current Rating 19A	Features	Shielded
	Voltage - Rated	-
Report errors?	Current Rating	19A
		Report errors?

EEG.3K.305.CYM Guarantees



Quality Guarantees

We provide 90 days warranty. *

If the items you received were not in perfect quality, we would be responsible for your refund or replacement, but the items must be returned in their original condition.



Service Guarantees

We guarantee 100% customer satisfaction.

Our experienced sales team and tech support team back our services to satisfy all our customers.

EEG.3K.305.CYM Payment Methods



















EEG.3K.305.CYM Shipping Methods













If you have any question about EEG.3K.305.CYM, please do not hesitate to contact us!

Website: https://www.heisener.com E-mail: salesdept@heisener.com